



Fuse-link, LV, 16 A, AC 400 V, NH000, gFF, IEC, dual indicator, insulated gripping lugs

Catalog No. 16NHFF000BI-400

Delivery program

Product range			Fuse
Field of application			low voltage
Rated current	I	A	16
Rated voltage			AC 400 V
Construction size			NH000
Utilization category			gFF
Status indicator			dual indicator
Description			insulated gripping lugs
Breaking Capacity		kA	120
Standard/Approval			IEC
Shape			square-body with knife blade contacts
Standards/Regulations			IEC 60269-1
Optional accessories			fuse-holder SD00-D and SD00-S

Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	I_n	A	16
Equipment heat dissipation, current-dependent	P_{vid}	W	2.1

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ec1@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			NH000
Rated current		A	16
Rated voltage		V	400
Voltage type			
Rated switching capacity		kA	
Utilization category			Other
Type of fuse status indicator			Combination fuse status indicator
Insulated metal gripping lugs (IMGL)			Yes

Assets (links)

Declaration of CE Conformity

00003257