



Fuse-link, high speed, 400 A, AC 690 V, DIN 00, aR, DIN, IEC, single indicator, live gripping lugs

170M2621

Product name		Eaton Bussmann series high speed square body fuse
Part no.		170M2621
EAN		5027590442312
Product Length/Depth		98 millimetre
Product height		51 millimetre
Product width		28 millimetre
Product weight		230.333333 gram
Compliances		CE Marked RoHS Compliant
Certifications		UL Recognized IEC Rated
Product Tradename		None
Product Type		High speed square body fuse
Product Sub Type		None
Amperage Rating		400 A
Voltage rating		690 V (IEC), 700 V (UL)
Interrupt rating		200 kAIC
Class		Class aR
Clearing (I ₂ T)		125000 at 660 V
Application		Semiconductor, DC Common bus, DC drives, power converters/rectifiers
Fuse type		DIN 43653 /80 Visual indicator
Fuse indicator		Top fuse status indicator
Fuse size		00

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		00
Type of current		AC
Rated voltage AC	V	690
Rated voltage DC	V	
Rated current	A	400
Utilization category		aR (accompanied semiconductor protection)
Breaking capacity	kA	200
Colour code		None
Type of fuse status indicator		Top fuse status indicator
Power loss at rated current	W	70
Mounting holes		M10
Centre-to-centre distance of connections	mm	78