

Continuous light module;white; LED;120 V

Part no. SL7-L120-W
171470
EL Number 4137724
(Norway)

General specifications	
Product name	Eaton Moeller® series SL7 Continuous light module
Part no.	SL7-L120-W
EAN	4015081679577
Product Length/Depth	73 millimetre
Product height	73 millimetre
Product width	73 millimetre
Product weight	0.082 kilogram
Certifications	UL 508 Certified by UL for use in Canada UL File No.: E29184 CSA Class No.: NKCR7 CSA-C22.2 No. 14-10 UL Category Control No.: NKCR UL report applies to both US and Canada UL IEC/EN 60947-5-1 CSA-C22.2 No. 94-91 IEC/EN 60529 CE
Product Tradename	SL7
Product Type	Continuous light module
Product Sub Type	None
Features & Functions	
Color	Other
Enclosure color	Black
Functions	Continuous light
Light modules	LED
Number of modules	Max. 5 (with standard base) Max. 10 (with base for mounting on both sides)
General information	
Connection to SmartWire-DT	No
Current consumption	0.028 - 0.031 A, at 110/120 V AC
Degree of protection	NEMA 4X IP66
Lifespan, electrical	100,000 h
Light type	Continuous light
Material	Cap: Polycarbonate (PC) Enclosure: Polycarbonate (PC)
Mounting position	As required
Overvoltage category	III
Pollution degree	3
Product Category	SL signal towers
Radiation angle	360 °
Rated impulse withstand voltage (Uimp)	4000 V AC
Shock resistance	15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27
Type	Continuous light module
Voltage type	AC
Climatic environmental conditions	
Ambient operating temperature - min	-30 °C
Ambient operating temperature - max	60 °C
Climatic proofing	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78

Electrical rating		
Leakage current		0.003 A
Rated insulation voltage (Ui)		250 V
Rated operational voltage (Ue) at AC - min		110 V
Rated operational voltage (Ue) at AC - max		120 V
Rated operational voltage (Ue) at DC - min		0 V
Rated operational voltage (Ue) at DC - max		0 V

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Optical module for signal tower (EC000232)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Optical module for signal tower (ecl@ss13-27-37-12-20 [AKF038019])		
Function		Continuous light
Repetition frequency settable		No
Colour		Other
Outer diameter	mm	73
Operating voltage AC 50 Hz	V	110 - 120
Operating voltage AC 60 Hz	V	110 - 120
Operating voltage DC	V	0 - 0
Voltage type		AC
Power consumption	W	
Lamp type		LED
Housing colour		Black
Degree of protection (IP)		IP66
Degree of protection (NEMA)		4X