

Auxiliary contact, SmartWire-DT

Part no. **MCB-HK-SWD**
177175
EL Number **1666609**
(Norway)

General specifications		
Product name		Eaton Distribution parts
Part no.		MCB-HK-SWD
EAN		4015081716197
Product Length/Depth		88.3 millimetre
Product height		74.7 millimetre
Product width		29.9 millimetre
Product weight		0.04 kilogram
Compliances		RoHS conform
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Accessory/spare part type		SWD interface module
Additional equipment required		Signaling switch
Ambient operating temperature - max		40 °C
Ambient operating temperature - min		-5 °C
Application		Switchgear for industrial and advanced commercial applications
Assembly width		1
Device fitting		Universal
EL number		1666609
Functions		Auxiliary switch
Number of contacts (change-over contacts)		0
Number of contacts (normally closed contacts)		0
Number of contacts (normally open contacts)		0
Number of poles at main contact unit - max		0
Number of switches (fault signal)		0
Rated operational voltage (Ue) - max		15 V
Rated switch current		0.0263 A
Suitable for current of main contact unit - max		0 A
Type		Accessory Accessory for combined residual current/power circuit breaker Accessory for miniature circuit breaker Accessory for residual current circuit breaker
Used with		SWD interface module Accessory Accessory for miniature circuit breaker Accessory for residual current circuit breaker Accessory for combined residual current/power circuit breaker
Voltage type		DC

Technical data ETIM 9.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)		
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss13-27-14-35-02 [AKE327018])		
Device fitting		Universal
Function		Auxiliary switch
Width in number of modular spacings		1

Number of contacts as normally open contact		0
Number of contacts as normally closed contact		0
Number of contacts as change-over contact		0
Number of fault-signal switches		0
Rated switch current	A	0.0263
Rated voltage	V	15
Voltage type		DC
With auto test for earth leakage function		No
Suitable for max. number of poles main contact unit (total)		0
Suitable for max. current main contact unit	A	0