DATASHEET - FAZ6-B2,5/1N



Miniature circuit breaker (MCB), 2.5 A, 1p+N, characteristic: B, 6 kA

Powering Business Worldwide

FAZ6-B2,5/1N Part no. Catalog No. 177498

Similar to illustration

Design verification as per IEC/EN 61439

| In | Α | 2.5 |
|------------------|---|--|
| P _{vid} | W | 1.7 |
| | | |
| | | |
| | | Meets the product standard's requirements. |
| | | Meets the product standard's requirements. |
| | | Meets the product standard's requirements. |
| | | Meets the product standard's requirements. |
| | | Meets the product standard's requirements. |
| | | Does not apply, since the entire switchgear needs to be evaluated. |
| | | Does not apply, since the entire switchgear needs to be evaluated. |
| | | Meets the product standard's requirements. |
| | | Does not apply, since the entire switchgear needs to be evaluated. |
| | | Meets the product standard's requirements. |
| | | Does not apply, since the entire switchgear needs to be evaluated. |
| | | Does not apply, since the entire switchgear needs to be evaluated. |
| | | Is the panel builder's responsibility. |
| | | Is the panel builder's responsibility. |
| | | |
| | | Is the panel builder's responsibility. |
| | | Is the panel builder's responsibility. |
| | | Is the panel builder's responsibility. |
| | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| | | Is the panel builder's responsibility. The specifications for the switchgear must b observed. |
| | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |
| | | " |

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Miniature circuit breaker (MCB) (EC000042)

| Electric engineering, automation, process control engineering / Electrical installation, device / Miniature circuit breaker system (MCB) / Miniature circuit breaker (MCB) (ecl@ss10.0.1-27-14-19-01 [AAB905014]) | | | | |
|---|---|----|-----|--|
| Release characteristic | | | В | |
| Number of poles (total) | | | 2 | |
| Number of protected poles | | | 1 | |
| Rated current | A | 4 | 2.5 | |
| Rated voltage | V | V | 240 | |
| Rated insulation voltage Ui | V | V | 440 | |
| Rated impulse withstand voltage Uimp | k | κV | 4 | |
| Rated short-circuit breaking capacity Icn EN 60898 at 230 V | k | kΑ | 6 | |
| Rated short-circuit breaking capacity Icn EN 60898 at 400 V | k | kΑ | 6 | |
| Rated short-circuit breaking capacity Icu IEC 60947-2 at 230 V | k | κA | 10 | |

| Rated short-circuit breaking capacity Icu IEC 60947-2 at 400 V $$ | kA | 10 |
|---|-----|----------|
| Voltage type | | AC |
| Frequency | Hz | 50 - 60 |
| Current limiting class | | 3 |
| Suitable for flush-mounted installation | | No |
| Concurrently switching N-neutral | | Yes |
| Over voltage category | | 3 |
| Pollution degree | | 2 |
| Additional equipment possible | | Yes |
| Width in number of modular spacings | | 2 |
| Built-in depth | mm | 70.5 |
| Degree of protection (IP) | | IP20 |
| Ambient temperature during operating | °C | -25 - 75 |
| Connectable conductor cross section multi-wired | mm² | 1 - 25 |
| Connectable conductor cross section solid-core | mm² | 1 - 25 |

Additional product information (links)

| Temperature dependency, derating | https://www.eaton.com/content/dam/eaton/technicaldocumentation/technical-data-tables/Derating table |
|----------------------------------|---|
| | FAZ6.pdf |