

Indicator light, RMQ-Titan, Flat, Blue, Metal bezel



**Part no.** M30C-FL-B  
**183284**  
**EL Number** 4315653  
**(Norway)**

General specifications		
Product name		Eaton Moeller® series M30 Indicator light
Part no.		M30C-FL-B
EAN		4015081782253
Product Length/Depth		36 millimetre
Product height		32 millimetre
Product width		46 millimetre
Product weight		0.035 kilogram
Certifications		IEC/EN 60947 VDE 0660
Product Tradename		M30
Product Type		Indicator light
Product Sub Type		None
Features & Functions		
Bezel color		Chrome
Bezel material		Metal
Design		Flat
Fitted with:		Front ring
Lens color		Blue
General information		
Degree of protection		NEMA 4X, 13
Degree of protection (front side)		IP67/IP69K
Opening diameter		30 mm
Overvoltage category		III
Pollution degree		3
Product category		RMQ-Titan
Rated impulse withstand voltage (Uimp)		4000 V AC
Size		Front dimensions: Ø 36 mm
Type		Indicator lights
Ambient conditions, mechanical		
Mounting position		As required
Shock resistance		Not planned
Climatic environmental conditions		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Climatic proofing		Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Terminal capacities		
Terminal capacity		0.5 - 1.5 mm <sup>2</sup> , solid 0.5 - 1.5 mm <sup>2</sup> , stranded
Electrical rating		
Rated insulation voltage (Ui)		250 V
Communication		
Connection to SmartWire-DT		With SWD-RMQ connections Yes
Contacts		
Force for positive opening - min		0 N

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Front element for indicator light (EC000223)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for warning lights (ecl@ss13-27-37-12-11 [AKF029019])		
Suitable for number of built-in signal lights		1
Colour lens		Blue
Construction type lens		Round
Hole diameter	mm	30
Width opening	mm	0
Height opening	mm	30
With front ring		Yes
Material front ring		Metal
Colour front ring		Chrome
Type of lens		Flat
Degree of protection (IP), front side		IP67/IP69K
Degree of protection (NEMA)		4X, 13