



**Connections, front, 1600A, IZMX40, 4 p, fixed mounted design**

**Part no.** IZMX-TF404-1600F-1  
**Catalog No.** 184180  
**Alternate Catalog No.** 67C2975H04  
**EL-Nummer (Norway)** 0004398523

**Delivery program**

Product range			Accessories
Accessories			Main terminal kits
Accessories			Front connections
			This connection kit comes with front terminals for connection to the circuit-breaker. The circuit-breaker can be connected directly with CU bars on the rear flanged connection. If necessary, the optional front terminals can be installed before the circuit-breaker is installed in the enclosure. This way, the final connection to the circuit-breaker can be made from the front.
Rated current	$I_n$	A	800 - 1600
Pole			4
For use with			IZMX40...4...08F IZMX40...4...10F IZMX40...4...12F IZMX40...4...16F INX40...4...08F INX40...4...10F INX40...4...12F INX40...4...16F
Information about equipment supplied			Each set includes the connections for top and bottom. 3-pole for 6 connections, 4-pole for 8 connections Screws, washers, and supports are included as standard.
Installation type			Fixed


**Design verification as per IEC/EN 61439**

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

**Technical data ETIM 7.0**

Low-voltage industrial components (EG000017) / Connection vane/phase spreader (EC002019)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Connection vane/phase spreader (ecl@ss10.0.1-27-37-13-05 [ACN990012])			
Suitable for number of poles			4

## Dimensions



② Contact surface flange terminal