Surface-mounting enclosure, RAL 1004, With additional cable entry in front for M22-XPV60... illuminated ring, Number of locations: 1, Cable entry: rear: $1 \times M20$, lateral: $1 \times M20$



Part no. M22-IY1-XPV60-* 197630

eneral specifications	
Product name	Eaton Moeller® series M22 Accessory Surface mounting enclosure
Part no.	M22-IY1-XPV60-*
Product Length/Depth	70 millimetre
Product height	30 millimetre
Product width	80 millimetre
Product weight	0.157 kilogram
Compliances	CE
Product Tradename	M22
Product Type	Accessory
Product Sub Type	Surface mounting enclosure
Catalog Notes	Individually markable with pushbutton configurator
eatures & Functions	
Enclosure color	Yellow
Enclosure material	Plastic
Fitted with:	High-grade steel screws Cable entry in front for M22-XPV60
Knockouts	1 x M20 (cable entry knockout at the side) 1 x M20 (cable entry knockouts at the rear)
Number of locations	1
RAL-number	1004
eneral information	
Degree of protection	IP67/IP69K NEMA 4X
Opening diameter	22.5 mm
ommunication	
Connection to SmartWire-DT	No

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Enclosure for control circuit devices (EC000200)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Housing for command and alarm devices (ecl@ss13-27-37-12-05 [AKF023019])

2		
Number of command positions		1
Construction type housing		Surface mounted housing
Housing material		Plastic
Housing material quality		Other
Diameter openings	mm	22.5
Colour housing cover		Yellow
Degree of protection (IP)		IP67/IP69K
Degree of protection (NEMA)		4X
Width	mm	80
Height	mm	30
Depth	mm	70