

Button lens, raised blue, blank



Part no. **M22-XDLH-B**
216451

| General specifications | | |
|--|--|--|
| Product name | | Eaton Moeller® series M22 Accessory Button lens |
| Part no. | | M22-XDLH-B |
| EAN | | 4015082164515 |
| Product Length/Depth | | 24 millimetre |
| Product height | | 9 millimetre |
| Product width | | 24 millimetre |
| Product weight | | 0.002 kilogram |
| Compliances | | Contact Manufacturer |
| Certifications | | CE |
| Product Tradename | | M22 |
| Product Type | | Accessory |
| Product Sub Type | | Button lens |
| Features & Functions | | |
| Design | | High |
| Inscription | | Individual inscription possible: ≤ 5 characters: letter height 5 mm Individual inscription possible: > 5 characters: letter height 3 mm |
| Lens color | | Blue |
| General information | | |
| Type | | Raised |
| Used with | | M22(S)-D-X M22(S)-DR-X M22-DG-X |
| Climatic environmental conditions | | |
| Ambient operating temperature - max | | 70 °C |
| Design verification | | |
| Equipment heat dissipation, current-dependent P _{vid} | | 0 W |
| Heat dissipation capacity P _{diss} | | 0 W |
| Heat dissipation per pole, current-dependent P _{vid} | | 0 W |
| Rated operational current for specified heat dissipation (I _n) | | 0 A |
| 10.2.2 Corrosion resistance | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | Please enquire |
| 10.2.5 Lifting | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | Not applicable. |
| 10.11 Short-circuit rating | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |

| | | | |
|-------------------------------------|--|--|--|
| 10.12 Electromagnetic compatibility | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 9.0

| | | | |
|---|--|----|-------|
| Low-voltage industrial components (EG000017) / Hood/lens for circuit control devices (EC001072) | | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Dome, refractor (ec1@ss13-27-37-12-31 [AKF049019]) | | | |
| Colour lens | | | Blue |
| Shape of lens | | | Round |
| Construction type | | | High |
| Labelled | | | No |
| Built-in diameter | | mm | 22.5 |
| Diameter | | mm | 22.2 |
| Width | | mm | 24 |
| Height | | mm | 9 |