

## Flush mounting plate, 5 mounting locations

**Part no.** M22-E5  
**216546**  
**EL Number** 4355395  
**(Norway)**

<b>General specifications</b>		
Product name		Eaton Moeller® series M22 Accessory Flush mounting plate
Part no.		M22-E5
EAN		4015082165468
Product Length/Depth		3 millimetre
Product height		72 millimetre
Product width		204 millimetre
Product weight		0.186 kilogram
Certifications		UL File No.: E29184 CSA File No.: 012528 CSA-C22.2 No. 94-91 UL UL 508 CE CSA Class No.: 3211-03 IEC/EN 60947-5 UL Category Control No.: NKCR CSA CSA-C22.2 No. 14-05
Product Tradename		M22
Product Type		Accessory
Product Sub Type		Flush mounting plate
<b>Features &amp; Functions</b>		
Color		Gray
Material		Aluminum
Number of locations		5
RAL-number		7035
<b>General information</b>		
Degree of protection		IP65 Only in conjunction with a suitable enclosure and correct mounting NEMA 4X, 13
Opening diameter		22 mm
Type		Surface mounting enclosure
<b>Climatic environmental conditions</b>		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
<b>Communication</b>		
Connection to SmartWire-DT		No
<b>Contacts</b>		
Force for positive opening - min		0 N
<b>Design verification</b>		
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdiss		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		0 A
Static heat dissipation, non-current-dependent Pvs		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		Not applicable.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Built-in panel for command devices (EC000201)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Installation plate for command devices (ecl@ss13-27-37-12-03 [ACO025016])			
Width		mm	204
Height		mm	72
Material			Aluminium
Number of command positions			5
Diameter openings		mm	22
Colour			Grey
Degree of protection (IP)			IP65
Degree of protection (NEMA)			4X, 13