

Illuminated selector switch actuator, RMQ-Titan, With thumb-grip, maintained, 3 positions, red, Bezel: titanium

Part no. M22-WRLK3-R

216845

**EL Number
(Norway)**

4355759

General specifications		
Product name		Eaton Moeller® series M22 Illuminated selector switch actuator
Part no.		M22-WRLK3-R
EAN		4015082168452
Product Length/Depth		46 millimetre
Product height		30 millimetre
Product width		30 millimetre
Product weight		0.013 kilogram
Compliances		CE Marked
Certifications		UL 508 IEC 60947-5 CSA Std. C22.2 No. 14-05 EN 60947-5 CSA Std. C22.2 No. 94-91 VDE VDE 0660 CSA-C22.2 No. 14-05 UL CSA File No.: 012528 CSA CE IEC/EN 60947-5 UL File No.: E29184 CSA-C22.2 No. 94-91 UL Category Control No.: NKCR CSA Class No.: 3211-03 IEC/EN 60947
Product Tradename		M22
Product Type		Illuminated selector switch actuator
Product Sub Type		None
Features & Functions		
Bezel color		Titanium
Bezel material		Plastic
Color		Red
Design		With thumb-grip
Fitted with:		Front ring
Functions		Stay-put/spring-return function, can be changed with coding parts M22-XC-Y
General information		
Accessories		Thumb grip
Degree of protection		NEMA 4X, 13
Degree of protection (front side)		IP66
Lifespan, mechanical		100,000 Operations
Opening diameter		22.5 mm
Operating frequency		2000 Operations/h
Operating torque		0.3 N-m
Product category		RMQ-Titan
Size		Front diameter: 29.7 mm
Suitable for		Illumination
Switching angle		60 °
Type		Illuminated selector switch actuator
Ambient conditions, mechanical		
Mounting position		As required
Shock resistance		30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27

Climatic environmental conditions		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Climatic proofing		Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Communication		
Connection to SmartWire-DT		With SWD-RMQ connections Yes
Actuator		
Actuator color		Black
Actuator function		Switching function latching Maintained
Actuator type		Toggle
Number of switch positions		3
Contacts		
Force for positive opening - min		0 N
Design verification		
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		0 A
Static heat dissipation, non-current-dependent Pvs		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		Not applicable.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Front element for selector switch (EC000222)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for selector switches (ecl@ss13-27-37-12-13 [AKF031019])		
Number of switch positions		3
Type of control element		Toggle
Suitable for illumination		Yes
Colour control element		Black
Colour indicator light cap		Red
Construction type lens		Round

Hole diameter	mm	22.5
Width opening	mm	0
Height opening	mm	0
Switching function latching		Yes
Spring-return		No
With front ring		Yes
Material front ring		Plastic
Colour front ring		Titanium
Degree of protection (IP), front side		IP66
Degree of protection (NEMA)		4X, 13