

## Miniature circuit breaker (MCB), 16 A, 3p+N, characteristic: C, 6 kA

**Part no.**                    **FAZ6-C16/3N**  
**239173**

| <b>General specifications</b>                                   |  |   |
|---|--|---|
| Product name  |  | Eaton Moeller series xEffect - FAZ6 MCB |
| Part no.  |  | FAZ6-C16/3N                             |
| EAN   |  | 4015082391737                           |
| Product Length/Depth  |  | 85 millimetre                           |
| Product height  |  | 73 millimetre                           |
| Product width   |  | 70.8 millimetre                         |
| Product weight  |  | 0.456 kilogram                          |
| Compliances   |  | RoHS conform<br>CE Marked               |
| Product Tradename   |  | xEffect - FAZ6                          |
| Product Type  |  | MCB                                     |
| Product Sub Type  |  | None                                    |
| <b>Delivery program</b>   |  |   |
| Number of poles (total)   |  | 4                                       |
| Number of poles (protected)                                     |  | 3                                       |
| Release characteristic  |  | C                                       |
| Amperage Rating   |  | 16 A                                    |
| <b>Technical Data - Electrical</b>                              |  |   |
| Voltage type  |  | AC                                      |
| Voltage rating (IEC/EN 60898-1)                                 |  | 415 V                                   |
| Voltage rating (IEC/EN 60947-2)                                 |  | 400                                     |
| Rated operational voltage (Ue) - max                            |  | 230 V                                   |
| Operational voltage (IEC/EN 60947-2) - max                      |  | 400 V                                   |
| Operational voltage at DC (IEC/EN 60947-2) - max                |  | 60 V                                    |
| Rated insulation voltage (Ui)                                   |  | 440 V                                   |
| Rated impulse withstand voltage (Uimp)                          |  | 4 kV                                    |
| Frequency rating - min  |  | 50 Hz                                   |
| Frequency rating - max  |  | 60 Hz                                   |
| Rated switching capacity (IEC/EN 60947-2)                       |  | 7.5 kA                                  |
| Rated service short-circuit breaking capacity (IEC/EN 60898-1)  |  | 6 kA                                    |
| Rated service short-circuit breaking capacity (IEC/EN 60947-2)  |  | 10 kA                                   |
| Rated short-circuit breaking capacity (EN 60898) at 230 V       |  | 6 kA                                    |
| Rated short-circuit breaking capacity (EN 60898) at 400 V       |  | 6 kA                                    |
| Rated short-circuit breaking capacity (IEC 60947-2) at 230 V    |  | 10 kA                                   |
| Rated short-circuit breaking capacity (IEC 60947-2) at 400 V    |  | 10 kA                                   |
| Overvoltage category  |  | III                                     |
| Pollution degree  |  | 2                                       |
| <b>Technical Data - Mechanical</b>                              |  |   |
| Width in number of modular spacings                             |  | 4                                       |
| Built-in depth  |  | 70.5 mm                                 |
| Degree of protection  |  | IP20                                    |
| Connectable conductor cross section (solid-core) - min          |  | 1 mm <sup>2</sup>                       |
| Connectable conductor cross section (solid-core) - max          |  | 25 mm <sup>2</sup>                      |
| Connectable conductor cross section (multi-wired) - min         |  | 1 mm <sup>2</sup>                       |
| Connectable conductor cross section (multi-wired) - max         |  | 25 mm <sup>2</sup>                      |
| <b>Design verification as per IEC/EN 61439 - technical data</b> |  |   |
| Rated operational current for specified heat dissipation (In)   |  | 16 A                                    |

|  |  |  |
|--|--|--|
| Equipment heat dissipation, current-dependent                                    |  | 7.2 W  |
| Ambient operating temperature - min  |  | -25 °C   |
| Ambient operating temperature - max  |  | 75 °C  |
| <b>Design verification as per IEC/EN 61439</b>                                   |  |  |
| 10.2.2 Corrosion resistance  |  | Meets the product standard's requirements.   |
| 10.2.3.1 Verification of thermal stability of enclosures                         |  | Meets the product standard's requirements.   |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat       |  | Meets the product standard's requirements.   |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects |  | Meets the product standard's requirements.   |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                 |  | Meets the product standard's requirements.   |
| 10.2.5 Lifting   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.6 Mechanical impact   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.7 Inscriptions  |  | Meets the product standard's requirements.   |
| 10.3 Degree of protection of assemblies  |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.4 Clearances and creepage distances   |  | Meets the product standard's requirements.   |
| 10.5 Protection against electric shock   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.6 Incorporation of switching devices and components                           |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.7 Internal electrical circuits and connections                                |  | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors   |  | Is the panel builder's responsibility.   |
| 10.9.2 Power-frequency electric strength   |  | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage   |  | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material                         |  | Is the panel builder's responsibility.   |
| 10.10 Temperature rise   |  | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating   |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.12 Electromagnetic compatibility  |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.13 Mechanical function  |  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |
| <b>Additional information</b>  |  |  |
| Current limiting class   |  | 3  |
| Features   |  | Additional equipment possible<br>Concurrently switching N-neutral  |

## Technical data ETIM 9.0

|   |    |         |
|---|----|---------|
| Circuit breakers and fuses (EG000020) / Miniature circuit breaker (MCB) (EC000042)  |    |         |
| Electric engineering, automation, process control engineering / Electrical installation, device / Miniature circuit breaker system (MCB) / Miniature circuit breaker (MCB) (ec1@ss13-27-14-19-01 [AAB905019]) |    |         |
| Built-in depth  | mm | 70.5    |
| Release characteristic  |    | C       |
| Number of poles (total)   |    | 4       |
| Number of protected poles   |    | 3       |
| Rated current   | A  | 16      |
| Rated voltage   | V  | 230     |
| Rated insulation voltage Ui   | V  | 440     |
| Rated impulse withstand voltage Uimp  | kV | 4       |
| Rated short-circuit breaking capacity Icn according to EN 60898 at 230 V  | kA | 6       |
| Voltage type  |    | AC      |
| Rated short-circuit breaking capacity Icn according to EN 60898 at 400 V  | kA | 6       |
| Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 230 V   | kA | 10      |
| Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 400 V   | kA | 10      |
| Frequency   | Hz | 50 - 60 |
| Power loss  | W  | 7.5     |
| Current limiting class  |    | 3       |
| Flush-mounted installation  |    | No      |
| Concurrently switching neutral conductor  |    | Yes     |
| Over voltage category   |    | 3       |

|   |  |                 |          |
|---|--|-----------------|----------|
| Pollution degree                                |  |                 | 2        |
| Additional equipment possible                   |  |                 | Yes      |
| Width in number of modular spacings             |  |                 | 4        |
| Degree of protection (IP)                       |  |                 | IP20     |
| Ambient temperature during operating            |  | °C              | -25 - 75 |
| Connectable conductor cross section multi-wired |  | mm <sup>2</sup> | 1 - 25   |
| Connectable conductor cross section solid-core  |  | mm <sup>2</sup> | 1 - 25   |
| Explosion-proof                                 |  |                 | No       |