

**Contactors, 3 pole, 380 V 400 V 75 kW, RAC 440: 380 - 440 V 50/60 Hz, AC operation, Screw terminals**



**Part no. DILM150(RAC440)  
239589**

<b>General specifications</b>		
Product name		Eaton Moeller® series DILM contactor
Part no.		DILM150(RAC440)
EAN		4015082395896
Product Length/Depth		160 millimetre
Product height		170 millimetre
Product width		90 millimetre
Product weight		2.25 kilogram
Compliances		CE Marked
Certifications		EN 60947-4-1 IEC 60947-4-1 UL 508 CSA Std. C22.2 No. 14-05 VDE CSA Class No.: 2411-03, 3211-04 CE VDE 0660 UL File No.: E29096 IEC/EN 60947 CSA UL Category Control No.: NLDX CSA File No.: 012528 UL 60947-4-1 UL IEC/EN 60947-4-1 CSA-C22.2 No. 60947-4-1-14
Product Tradename		DILM
Product Type		Contactors
Product Sub Type		None
Catalog Notes		Contacts according to EN 50012
<b>Features &amp; Functions</b>		
Fitted with:		Suppressor circuit in actuating electronics
<b>General information</b>		
Application		Contactors for Motors
Degree of protection		IP00
Frame size		FS4
Lifespan, mechanical		10,000,000 Operations (AC operated)
Operating frequency		3600 mechanical Operations/h (AC operated)
Overvoltage category		III
Pollution degree		3
Product category		Contactors
Protection		Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
Rated impulse withstand voltage (Uimp)		8000 V AC
Residual current		1 mA (with actuation of A1 - A2 by the electronics with "0" signal)
Resistance per pole		0.6 mΩ
Suitable for		Also motors with efficiency class IE3
Utilization category		AC-3: Normal AC induction motors: starting, switch off during running AC-1: Non-inductive or slightly inductive loads, resistance furnaces AC-4: Normal AC induction motors: starting, plugging, reversing, inching
Voltage type		AC
<b>Ambient conditions, mechanical</b>		
Shock resistance		10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

		5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms 7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms 5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms
<b>Climatic environmental conditions</b>		
Altitude		Max. 2000 m
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		60 °C
Ambient operating temperature (enclosed) - min		25 °C
Ambient operating temperature (enclosed) - max		40 °C
Ambient storage temperature - min		40 °C
Ambient storage temperature - max		80 °C
Climatic proofing		Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
<b>Electro magnetic compatibility</b>		
Emitted interference		According to EN 60947-1
Interference immunity		According to EN 60947-1
<b>Terminal capacities</b>		
Terminal capacity (copper band)		2 x (6 x 16 x 0.8) mm (Number of segments x width x thickness), Main cables
Terminal capacity (flexible with ferrule)		1 x (10 - 95) mm <sup>2</sup> , Main cables 2 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables 1 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables 2 x (10 - 70) mm <sup>2</sup> , Main cables
Terminal capacity (solid)		2 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables 1 x (0.75 - 4) mm <sup>2</sup> , Control circuit cables
Terminal capacity (solid/stranded AWG)		Single 8...3/0, double 8...2/0, Main cables 18 - 14, Control circuit cables
Terminal capacity (stranded)		2 x (16 - 70) mm <sup>2</sup> , Main cables 1 x (16 - 95) mm <sup>2</sup> , Main cables
Stripping length (main cable)		24 mm
Stripping length (control circuit cable)		10 mm
Screw size		M3.5, Terminal screw, Control circuit cables 5 mm AF, Hexagon socket-head spanner, Terminal screw, Main cables M10, Terminal screw, Main cables
Screwdriver size		0.8 x 5.5/1 x 6 mm, Terminal screw, Control circuit cables, Standard screwdriver 2, Terminal screw, Control circuit cables, Pozidriv screwdriver
Tightening torque		14 Nm, Screw terminals, Main cables 1.2 Nm, Screw terminals, Control circuit cables
<b>Electrical rating</b>		
Rated breaking capacity at 220/230 V		1500 A
Rated breaking capacity at 380/400 V		1500 A
Rated breaking capacity at 500 V		1500 A
Rated breaking capacity at 660/690 V		1200 A
Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V		190 A
Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V		150 A
Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V		150 A
Rated operational current (Ie) at AC-3, 440 V		150 A
Rated operational current (Ie) at AC-3, 500 V		150 A
Rated operational current (Ie) at AC-3, 660 V, 690 V		100 A
Rated operational current (Ie) at AC-4, 220 V, 230 V, 240 V		65 A
Rated operational current (Ie) at AC-4, 440 V		65 A
Rated operational current (Ie) at AC-4, 500 V		65 A
Rated operational current (Ie) at AC-4, 660 V, 690 V		50 A
Rated operational current (Ie) at DC-1, 60 V		160 A
Rated operational current (Ie) at DC-1, 110 V		160 A
Rated operational current (Ie) at DC-1, 220 V		90 A
Rated insulation voltage (Ui)		690 V
Rated making capacity up to 690 V (cos phi to IEC/EN 60947)		2100 A

Rated operational power at AC-3, 240 V, 50 Hz	52 kW
Rated operational power at AC-3, 380/400 V, 50 Hz	75 kW
Rated operational power at AC-3, 415 V, 50 Hz	91 kW
Rated operational power at AC-3, 440 V, 50 Hz	95 kW
Rated operational power at AC-3, 500 V, 50 Hz	110 kW
Rated operational power at AC-3, 690 V, 50 Hz	96 kW
Rated operational power at AC-4, 220/230 V, 50 Hz	20 kW
Rated operational power at AC-4, 240 V, 50 Hz	22 kW
Rated operational power at AC-4, 415 V, 50 Hz	39 kW
Rated operational power at AC-4, 440 V, 50 Hz	41 kW
Rated operational power at AC-4, 500 V, 50 Hz	47 kW
Rated operational power at AC-4, 660/690 V, 50 Hz	48 kW
Rated operational voltage (Ue) at AC - max	690 V
<b>Short-circuit rating</b>	
Short-circuit current rating (basic rating)	600 A, max. CB, SCCR (UL/CSA) 10 kA, SCCR (UL/CSA) 600 A, max. Fuse, SCCR (UL/CSA)
Short-circuit current rating (high fault at 480 V)	65 kA, CB, SCCR (UL/CSA) 300/300 A, Class J, max. Fuse, SCCR (UL/CSA) 250 A, max. CB, SCCR (UL/CSA) 30/100 kA, Fuse, SCCR (UL/CSA)
Short-circuit current rating (high fault at 600 V)	30/100 kA, Fuse, SCCR (UL/CSA) 300/600 A, Class J, max. Fuse, SCCR (UL/CSA) 350 A, max. CB, SCCR (UL/CSA) 30 kA, CB, SCCR (UL/CSA)
Short-circuit protection rating (type 1 coordination) at 400 V	250 A gG/gL
Short-circuit protection rating (type 1 coordination) at 690 V	250 A gG/gL
Short-circuit protection rating (type 2 coordination) at 400 V	250 A gG/gL
Short-circuit protection rating (type 2 coordination) at 690 V	250 A gG/gL
<b>Conventional thermal current I<sub>th</sub></b>	
Conventional thermal current I <sub>th</sub> (1-pole, enclosed)	360 A
Conventional thermal current I <sub>th</sub> (3-pole, enclosed)	144 A
Conventional thermal current I <sub>th</sub> at 55°C (3-pole, open)	170 A
Conventional thermal current I <sub>th</sub> at 60°C (3-pole, open)	160 A
Conventional thermal current I <sub>th</sub> of main contacts (1-pole, open)	400 A
<b>Switching capacity</b>	
Switching capacity (main contacts, general use)	225 A, Maximum motor rating (UL/CSA)
<b>Magnet system</b>	
Arcing time	15 ms
Drop-out voltage	AC operated: 0.6 - 0.25 x UC, AC operated
Duty factor	100 %
Pick-up voltage	0.8 - 1.15 V AC x U <sub>c</sub>
Power consumption, pick-up, 50 Hz	180 VA, Dual-frequency coil in a cold state and 1.0 x U <sub>s</sub> , at 50 Hz
Power consumption, pick-up, 60 Hz	170 VA, Dual-frequency coil in a cold state and 1.0 x U <sub>s</sub> , at 60 Hz
Power consumption, sealing, 50 Hz	3.1 VA, Dual-frequency coil in a cold state and 1.0 x U <sub>s</sub> , at 50 Hz 2.3 W, Dual-frequency coil in a cold state and 1.0 x U <sub>s</sub> , at 50 Hz
Power consumption, sealing, 60 Hz	2.3 W, Dual-frequency coil in a cold state and 1.0 x U <sub>s</sub> , at 60 Hz 3.1 VA, Dual-frequency coil in a cold state and 1.0 x U <sub>s</sub> , at 60 Hz
Rated control supply voltage (U <sub>s</sub> ) at AC, 50 Hz - min	380 V
Rated control supply voltage (U <sub>s</sub> ) at AC, 50 Hz - max	440 V
Rated control supply voltage (U <sub>s</sub> ) at AC, 60 Hz - min	380 V
Rated control supply voltage (U <sub>s</sub> ) at AC, 60 Hz - max	440 V
Rated control supply voltage (U <sub>s</sub> ) at DC - min	0 V
Rated control supply voltage (U <sub>s</sub> ) at DC - max	0 V
Switching time (AC operated, make contacts, closing delay) - min	28 ms
Switching time (AC operated, make contacts, closing delay) - max	33 ms
Switching time (AC operated, make contacts, opening delay) - min	35 ms
Switching time (AC operated, make contacts, opening delay) - max	41 ms
<b>Motor rating</b>	

Assigned motor power at 115/120 V, 60 Hz, 1-phase		10 HP
Assigned motor power at 200/208 V, 60 Hz, 3-phase		50 HP
Assigned motor power at 230/240 V, 60 Hz, 1-phase		30 HP
Assigned motor power at 230/240 V, 60 Hz, 3-phase		60 HP
Assigned motor power at 460/480 V, 60 Hz, 3-phase		125 HP
Assigned motor power at 575/600 V, 60 Hz, 3-phase		125 HP
<b>Communication</b>		
Connection		Screw terminals
Connection to SmartWire-DT		No
<b>Contacts</b>		
Number of auxiliary contacts (normally closed contacts)		0
Number of auxiliary contacts (normally open contacts)		0
<b>Safety</b>		
Safe isolation		690 V AC, Between the contacts, According to EN 61140 690 V AC, Between coil and contacts, According to EN 61140
<b>Special purpose ratings</b>		
Special purpose rating of ballast electrical discharge lamps		160 A (480V 60Hz 3phase, 277V 60Hz 1phase) 160 A (600V 60Hz 3phase, 347V 60Hz 1phase)
Special purpose rating of definite purpose rating		900 A, LRA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA) 150 A, FLA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA)
Special purpose rating of elevator control		30 HP, 200 V 60 Hz 3-ph, (UL/CSA) 92 A, 200 V 60 Hz 3-ph, (UL/CSA) 75 HP, 480 V 60 Hz 3-ph, (UL/CSA) 100 HP, 600 V 60 Hz 3-ph, (UL/CSA) 99 A, 600 V 60 Hz 3-ph, (UL/CSA) 104 A, 240 V 60 Hz 3-ph, (UL/CSA) 40 HP, 240 V 60 Hz 3-ph, (UL/CSA) 96 A, 480 V 60 Hz 3-ph, (UL/CSA)
Special purpose rating of refrigeration control (CSA only)		540 A, LRA 480 V 60 Hz 3phase; (CSA) 90 A, FLA 480 V 60 Hz 3phase; (CSA) 90 A, FLA 600 V 60 Hz 3phase; (CSA) 540 A, LRA 600 V 60 Hz 3phase; (CSA)
Special purpose rating of resistance air heating		160 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA) 160 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA)
Special purpose rating of tungsten incandescent lamps		160 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA) 160 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA)
<b>Design verification</b>		
Equipment heat dissipation, current-dependent Pvid		32.1 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		10.7 W
Rated operational current for specified heat dissipation (In)		150 A
Static heat dissipation, non-current-dependent Pvs		2.3 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss13-27-37-10-03 [AAB718020])		
Rated control supply voltage AC 50 Hz	V	380 - 440
Rated control supply voltage AC 60 Hz	V	380 - 440
Rated control supply voltage DC	V	0 - 0
Voltage type for actuating		AC
Number of normally closed contacts as main contact		0
Number of normally open contacts as main contact		3
Type of electrical connection of main circuit		Screw connection
Operating voltage AC 50 Hz	V	230 - 690
Operating voltage AC 60 Hz	V	230 - 690
Rated operation current I <sub>e</sub> at AC-1, 400 V	A	190
Rated operation current I <sub>e</sub> at AC-3, 400 V	A	150
Rated operation power at AC-3, 400 V	kW	75
Rated operation current I <sub>e</sub> at AC-4, 400 V	A	65
Rated operation power at AC-4, 400 V	kW	33
Rated operation power NEMA	kW	93
Number of auxiliary contacts as normally open contact		0
Number of auxiliary contacts as normally closed contact		0
Modular version		No
Width	mm	90
Height	mm	170
Depth	mm	160