

**Contactors, 3 pole, 380 V 400 V 55 kW, RAC 240: 190 - 240 V 50/60 Hz, AC operation, Spring-loaded terminals**



**Part no. DILMC115(RAC240)**

**239736**

**EL Number  
(Norway)**

**4110256**

General specifications		
Product name		Eaton Moeller® series DILM contactor
Part no.		DILMC115(RAC240)
EAN		4015082397364
Product Length/Depth		160 millimetre
Product height		170 millimetre
Product width		90 millimetre
Product weight		2.27 kilogram
Certifications		CSA-C22.2 No. 60947-4-1-14 UL File No.: E29096 UL VDE 0660 CSA UL 60947-4-1 IEC/EN 60947-4-1 CSA File No.: 012528 CE CSA Class No.: 2411-03, 3211-04 IEC/EN 60947 UL Category Control No.: NLDX
Product Tradename		DILM
Product Type		Contactors
Product Sub Type		None
Catalog Notes		Contacts according to EN 50012
Features & Functions		
Fitted with:		Suppressor circuit in actuating electronics
General information		
Application		Contactors for Motors
Degree of protection		IP00
Frame size		FS4
Lifespan, mechanical		10,000,000 Operations (AC operated)
Operating frequency		3600 mechanical Operations/h (AC operated)
Overvoltage category		III
Pollution degree		3
Product category		Contactors
Protection		Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
Rated impulse withstand voltage (Uimp)		8000 V AC
Residual current		1 mA (with actuation of A1 - A2 by the electronics with "0" signal)
Resistance per pole		0.6 mΩ
Suitable for		Also motors with efficiency class IE3
Utilization category		AC-1: Non-inductive or slightly inductive loads, resistance furnaces AC-4: Normal AC induction motors: starting, plugging, reversing, inching AC-3: Normal AC induction motors: starting, switch off during running
Voltage type		AC
Ambient conditions, mechanical		
Shock resistance		10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms 7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms 5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms

		5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
<b>Climatic environmental conditions</b>		
Altitude		Max. 2000 m
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		60 °C
Ambient operating temperature (enclosed) - min		25 °C
Ambient operating temperature (enclosed) - max		40 °C
Ambient storage temperature - min		40 °C
Ambient storage temperature - max		80 °C
Climatic proofing		Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
<b>Electro magnetic compatibility</b>		
Emitted interference		According to EN 60947-1
Interference immunity		According to EN 60947-1
<b>Terminal capacities</b>		
Terminals		Spring-cage terminals on auxiliary and control circuit terminals
Terminal capacity (copper band)		2 x (6 x 16 x 0.8) mm (Number of segments x width x thickness), Main cables
Terminal capacity (flexible with ferrule)		1 x (10 - 95) mm <sup>2</sup> , Main cables 2 x (10 - 70) mm <sup>2</sup> , Main cables 1 x (0.75 - 1.5) mm <sup>2</sup> 2 x (0.75 - 1.5) mm <sup>2</sup> , Control circuit cables, Spring-loaded terminals
Terminal capacity (flexible)		1 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables, Spring-loaded terminals 2 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables, Spring-loaded terminals
Terminal capacity (solid)		1 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables, Spring-loaded terminals 2 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables, Spring-loaded terminals
Terminal capacity (solid/stranded AWG)		18 - 14, Control circuit cables, Spring-loaded terminals Single 8...3/0, double 8...2/0, Main cables
Terminal capacity (stranded)		2 x (16 - 70) mm <sup>2</sup> , Main cables 1 x (16 - 95) mm <sup>2</sup> , Main cables
Stripping length (main cable)		24 mm
Stripping length (control circuit cable)		10 mm
Screw size		5 mm AF, Hexagon socket-head spanner, Terminal screw, Main cables M10, Terminal screw, Main cables
Screwdriver size		3.5 mm, Spring-loaded terminals, Control circuit cables
Tightening torque		14 Nm, Screw terminals, Main cables
<b>Electrical rating</b>		
Rated breaking capacity at 220/230 V		1150 A
Rated breaking capacity at 380/400 V		1150 A
Rated breaking capacity at 500 V		1150 A
Rated breaking capacity at 660/690 V		1100 A
Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V		160 A
Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V		115 A
Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V		115 A
Rated operational current (Ie) at AC-3, 440 V		115 A
Rated operational current (Ie) at AC-3, 500 V		115 A
Rated operational current (Ie) at AC-3, 660 V, 690 V		93 A
Rated operational current (Ie) at AC-4, 220 V, 230 V, 240 V		55 A
Rated operational current (Ie) at AC-4, 440 V		55 A
Rated operational current (Ie) at AC-4, 500 V		55 A
Rated operational current (Ie) at AC-4, 660 V, 690 V		45 A
Rated operational current (Ie) at DC-1, 60 V		160 A
Rated operational current (Ie) at DC-1, 110 V		160 A
Rated operational current (Ie) at DC-1, 220 V		90 A
Rated insulation voltage (Ui)		690 V
Rated making capacity up to 690 V (cos phi to IEC/EN 60947)		1610 A
Rated operational power at AC-3, 240 V, 50 Hz		40 kW
Rated operational power at AC-3, 380/400 V, 50 Hz		55 kW
Rated operational power at AC-3, 415 V, 50 Hz		70 kW

Rated operational power at AC-3, 440 V, 50 Hz	75 kW
Rated operational power at AC-3, 500 V, 50 Hz	85 kW
Rated operational power at AC-3, 690 V, 50 Hz	90 kW
Rated operational power at AC-4, 220/230 V, 50 Hz	17 kW
Rated operational power at AC-4, 240 V, 50 Hz	19 kW
Rated operational power at AC-4, 415 V, 50 Hz	33 kW
Rated operational power at AC-4, 440 V, 50 Hz	35 kW
Rated operational power at AC-4, 500 V, 50 Hz	40 kW
Rated operational power at AC-4, 660/690 V, 50 Hz	43 kW
Rated operational voltage (Ue) at AC - max	690 V
<b>Short-circuit rating</b>	
Short-circuit current rating (basic rating)	600 A, max. Fuse, SCCR (UL/CSA) 10 kA, SCCR (UL/CSA) 600 A, max. CB, SCCR (UL/CSA)
Short-circuit current rating (high fault at 480 V)	250 A, max. CB, SCCR (UL/CSA) 65 kA, CB, SCCR (UL/CSA) 30/100 kA, Fuse, SCCR (UL/CSA) 300/300 A, Class J, max. Fuse, SCCR (UL/CSA)
Short-circuit current rating (high fault at 600 V)	30 kA, CB, SCCR (UL/CSA) 300/300 A, Class J, max. Fuse, SCCR (UL/CSA) 30/100 kA, Fuse, SCCR (UL/CSA) 350 A, max. CB, SCCR (UL/CSA)
Short-circuit protection rating (type 1 coordination) at 400 V	250 A gG/gL
Short-circuit protection rating (type 1 coordination) at 690 V	250 A gG/gL
Short-circuit protection rating (type 2 coordination) at 400 V	250 A gG/gL
Short-circuit protection rating (type 2 coordination) at 690 V	250 A gG/gL
<b>Conventional thermal current Ith</b>	
Conventional thermal current Ith (1-pole, enclosed)	285 A
Conventional thermal current Ith (3-pole, enclosed)	115 A
Conventional thermal current Ith at 55°C (3-pole, open)	135 A
Conventional thermal current Ith at 60°C (3-pole, open)	130 A
Conventional thermal current Ith of main contacts (1-pole, open)	325 A
<b>Switching capacity</b>	
Switching capacity (main contacts, general use)	180 A, Maximum motor rating (UL/CSA)
<b>Magnet system</b>	
Arcing time	15 ms
Drop-out voltage	AC operated: 0.6 - 0.25 x UC, AC operated
Duty factor	100 %
Pick-up voltage	0.8 - 1.15 V AC x Uc
Power consumption, pick-up, 50 Hz	180 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz
Power consumption, pick-up, 60 Hz	170 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz
Power consumption, sealing, 50 Hz	2.3 W, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz 3.1 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz
Power consumption, sealing, 60 Hz	3.1 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz 2.3 W, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz
Rated control supply voltage (Us) at AC, 50 Hz - min	190 V
Rated control supply voltage (Us) at AC, 50 Hz - max	240 V
Rated control supply voltage (Us) at AC, 60 Hz - min	190 V
Rated control supply voltage (Us) at AC, 60 Hz - max	240 V
Rated control supply voltage (Us) at DC - min	0 V
Rated control supply voltage (Us) at DC - max	0 V
Switching time (AC operated, make contacts, closing delay) - min	28 ms
Switching time (AC operated, make contacts, closing delay) - max	33 ms
Switching time (AC operated, make contacts, opening delay) - min	35 ms
Switching time (AC operated, make contacts, opening delay) - max	41 ms
<b>Motor rating</b>	
Assigned motor power at 115/120 V, 60 Hz, 1-phase	10 HP
Assigned motor power at 200/208 V, 60 Hz, 3-phase	40 HP
Assigned motor power at 230/240 V, 60 Hz, 1-phase	25 HP

Assigned motor power at 230/240 V, 60 Hz, 3-phase		50 HP
Assigned motor power at 460/480 V, 60 Hz, 3-phase		100 HP
Assigned motor power at 575/600 V, 60 Hz, 3-phase		100 HP
<b>Communication</b>		
Connection		Spring-loaded terminals
Connection to SmartWire-DT		No
<b>Contacts</b>		
Number of auxiliary contacts (normally closed contacts)		0
Number of auxiliary contacts (normally open contacts)		0
<b>Safety</b>		
Safe isolation		690 V AC, Between coil and contacts, According to EN 61140 690 V AC, Between the contacts, According to EN 61140
<b>Special purpose ratings</b>		
Special purpose rating of ballast electrical discharge lamps		160 A (600V 60Hz 3phase, 347V 60Hz 1phase) 160 A (480V 60Hz 3phase, 277V 60Hz 1phase)
Special purpose rating of definite purpose rating		690 A, LRA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA) 115 A, FLA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA)
Special purpose rating of elevator control		30 HP, 200 V 60 Hz 3-ph, (UL/CSA) 104 A, 240 V 60 Hz 3-ph, (UL/CSA) 92 A, 200 V 60 Hz 3-ph, (UL/CSA) 99 A, 600 V 60 Hz 3-ph, (UL/CSA) 40 HP, 240 V 60 Hz 3-ph, (UL/CSA) 100 HP, 600 V 60 Hz 3-ph, (UL/CSA) 75 HP, 480 V 60 Hz 3-ph, (UL/CSA) 96 A, 480 V 60 Hz 3-ph, (UL/CSA)
Special purpose rating of refrigeration control (CSA only)		84 A, FLA 600 V 60 Hz 3phase; (CSA) 84 A, FLA 480 V 60 Hz 3phase; (CSA) 540 A, LRA 480 V 60 Hz 3phase; (CSA) 540 A, LRA 600 V 60 Hz 3phase; (CSA)
Special purpose rating of resistance air heating		160 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA) 160 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA)
Special purpose rating of tungsten incandescent lamps		160 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA) 160 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA)
<b>Design verification</b>		
Equipment heat dissipation, current-dependent Pvid		18.9 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		6.3 W
Rated operational current for specified heat dissipation (In)		115 A
Static heat dissipation, non-current-dependent Pvs		2.3 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss13-27-10-03 [AAB718020])		
Rated control supply voltage AC 50 Hz	V	190 - 240
Rated control supply voltage AC 60 Hz	V	190 - 240
Rated control supply voltage DC	V	0 - 0
Voltage type for actuating		AC
Number of normally closed contacts as main contact		0
Number of normally open contacts as main contact		3
Type of electrical connection of main circuit		Spring clamp connection
Operating voltage AC 50 Hz	V	230 - 690
Operating voltage AC 60 Hz	V	230 - 690
Rated operation current I <sub>e</sub> at AC-1, 400 V	A	160
Rated operation current I <sub>e</sub> at AC-3, 400 V	A	115
Rated operation power at AC-3, 400 V	kW	55
Rated operation current I <sub>e</sub> at AC-4, 400 V	A	55
Rated operation power at AC-4, 400 V	kW	28
Rated operation power NEMA	kW	74.6
Number of auxiliary contacts as normally open contact		0
Number of auxiliary contacts as normally closed contact		0
Modular version		No
Width	mm	90
Height	mm	170
Depth	mm	160