



**Undervoltage release, 115 V, delayed 0, 4N/O, 1HP**

**Part no.** Z-USD/115  
**Catalog No.** 248292  
**Alternate Catalog No.** Z-USD/115

Similar to illustration

**Delivery program**

Basic function			Accessories for miniature circuit-breaker
Basic function accessories			Undervoltage release
Application			Switchgear for industrial and advanced commercial applications
Tripping		s...	delayed 0.4 s
Product range			Accessory
Side mounting			for fitting on left to: FAZ
Contact sequence			

**Design verification as per IEC/EN 61439**

Technical data for design verification			
Operating ambient temperature min.		°C	-5
Operating ambient temperature max.		°C	40

**Technical data ETIM 7.0**

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)			
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss10.0.1-27-14-35-02 [AKE327013])			
Device fitting			Universal
Additional equipment			Under voltage coil
Attached at delivery			No
Assembly width (TE)			1
Number of contacts as normally open contact			1
Number of contacts as normally closed contact			1
Number of contacts as change-over contact			0
Number of fault-signal switches			0
Rated switch current		A	0
Rated voltage		V	115
Voltage type for actuating			AC
With auto test for earth leakage function			No
Suitable for max. number of poles main contact unit (total)			1
Suitable for max. current main contact unit		A	0

## Dimensions

