

Restarting device, 220-240VAC, 4HP



Part no. Z-FW-LP
248296
EL Number 1609476
(Norway)

General specifications	
Product name	Eaton Distribution parts
Part no.	Z-FW-LP
EAN	4015082482961
Product Length/Depth	80 millimetre
Product height	77.3 millimetre
Product width	88.4 millimetre
Product weight	0.298 kilogram
Compliances	RoHS conform
Product Tradename	None
Product Type	Distribution parts
Product Sub Type	None
Public Consumption	Yes
Product Family Description	ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable	Yes
Product Specification Details	
Accessory/spare part type	Restarting device
Additional equipment required	Monitoring unit with automatic reclosing
Ambient operating temperature - max	40 °C
Ambient operating temperature - min	-25 °C
Application	Switchgear for industrial and advanced commercial applications
Assembly width	4
Degree of protection	IP40
Device fitting	Universal
EL number	1609476
Enclosure width	80 mm
Equipment heat dissipation, current-dependent	0 W
Frame	Standard front dimension: 45 mm
Frequency rating	50 Hz / 60 Hz
Function selector	Automatic 5 x, OFF/RESET
Functions	Automatic restart With auto test for earth leakage function
Heat dissipation capacity	0 W
Heat dissipation per pole, current-dependent	0 W
Mounting width	70 mm
Number of contacts (change-over contacts)	0
Number of contacts (normally closed contacts)	0
Number of contacts (normally open contacts)	0
Number of poles at main contact unit - max	0
Number of switches (fault signal)	0
Rated operational current for specified heat dissipation (In)	0 A
Rated operational voltage (Ue) - max	230 V
Rated switch current	0 A
Relay output for alarm	5 A
Special features	Z-FW... (Test module (0.5 space unit) for remote testing of residual current devices)
Static heat dissipation, non-current-dependent	1.5 W
Suitable for current of main contact unit - max	0 A
Terminal capacity (cable)	2.5 mm ² (1x) 1.5 mm ² (2x)

Terminal capacity (solid wire)			1 mm ² - 2.5 mm ² 1.5 mm ² (2x)
Terminal protection			Protection against electric shock to A3, ÜVE-EN 6
Terminal type			Lift terminals
Type			Accessory Accessory for miniature circuit breaker Accessory for residual current circuit breaker
Used with			Restarting device Accessory for residual current circuit breaker Accessory Accessory for miniature circuit breaker
Voltage rating at AC			220 V AC - 240 V AC
Voltage type			AC

Technical data ETIM 9.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)			
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss13-27-14-35-02 [AKE327018])			
Device fitting			Universal
Function			
Width in number of modular spacings			4
Number of contacts as normally open contact			0
Number of contacts as normally closed contact			0
Number of contacts as change-over contact			0
Number of fault-signal switches			0
Rated switch current		A	0
Rated voltage		V	230
Voltage type			AC
With auto test for earth leakage function			Yes
Suitable for max. number of poles main contact unit (total)			0
Suitable for max. current main contact unit		A	0