

Shunt release, 110-415V, 1.5HP



**Part no.**                      **Z-BHASA/230**  
**248445**

General specifications		
Product name		Eaton Distribution parts
Part no.		Z-BHASA/230
EAN		4015082484453
Product Length/Depth		80 millimetre
Product height		75 millimetre
Product width		39.1 millimetre
Product weight		0.157 kilogram
Compliances		RoHS conform
Certifications		EN45545-2 IEC 61373
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Accessory/spare part type		Shunt release
Additional equipment required		Shunt release (for power circuit breaker)
Ambient operating temperature - max		40 °C
Ambient operating temperature - min		-5 °C
Application		Switchgear for industrial and advanced commercial applications
Assembly width		1.5
Device fitting		Miniature circuit breaker (MCB)
Functions		Shunt release (for power circuit breaker)
Number of contacts (change-over contacts)		0
Number of contacts (normally closed contacts)		1
Number of contacts (normally open contacts)		1
Number of poles at main contact unit - max		1
Number of switches (fault signal)		0
Rated operational voltage (Ue) - max		230 V
Rated switch current		1.7 A
Suitable for current of main contact unit - max		3.4 A
Type		Accessory Accessory for residual current circuit breaker
Used with		Shunt releases Accessory Accessory for residual current circuit breaker
Voltage type		AC/DC

**Technical data ETIM 9.0**

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)		
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss13-27-14-35-02 [AKE327018])		
Device fitting		Miniature circuit breaker (MCB)
Function		Shunt release (for power circuit breaker)
Width in number of modular spacings		1.5
Number of contacts as normally open contact		1
Number of contacts as normally closed contact		1
Number of contacts as change-over contact		0

Number of fault-signal switches		0
Rated switch current	A	1.7
Rated voltage	V	230
Voltage type		AC/DC
With auto test for earth leakage function		No
Suitable for max. number of poles main contact unit (total)		1
Suitable for max. current main contact unit	A	3.4