

Remote operator, 220-250VDC, for size 3



**Part no. NZM3-XR220-250DC  
259860**

<b>General specifications</b>		
Product name		Eaton Moeller series NZM remote operator
Part no.		NZM3-XR220-250DC
EAN		4015082598600
Product Length/Depth		170 millimetre
Product height		140 millimetre
Product width		140 millimetre
Product weight		3.194 kilogram
Compliances		IEC UL/CSA RoHS conform
Certifications		IEC60947 CSA (Class No. 1437-01) CSA certified CSA-C22.2 No. 5-09 UL (Category Control Number DIHS) CE marking UL489 CSA (File No. 22086) UL listed UL (File No. E140305)
Product Tradename		NZM
Product Type		Accessories
Product Sub Type		Remote operator
<b>Delivery program</b>		
Type		Accessory Remote operator, can be synchronized
Number of poles		Three-pole/Four-pole
Special features		Cannot be combined with switch-disconnector PN... M22-CK11(20/02) dual auxiliary switch cannot be combined with NZM3-XR... remote operator
Frame		NZM3
Used with		N(S)3(-4) NZM3(-4)
<b>Technical Data - Electrical</b>		
Voltage type		AC
Voltage rating		220 - 250 V DC
Operating voltage - min		0.85 x Us
Operating voltage - max		1.1 x Us
Rated control supply voltage (Us) at AC, 50 Hz - min		0 V
Rated control supply voltage (Us) at AC, 50 Hz - max		0 V
Rated control supply voltage (Us) at AC, 60 Hz - min		0 V
Rated control supply voltage (Us) at AC, 60 Hz - max		0 V
Rated control supply voltage (Us) at DC - min		220 V
Rated control supply voltage (Us) at DC - max		250 V
Voltage tolerance - min		0.85
Voltage tolerance - max		1.1
Power consumption		250 W (24 - 30 V DC)
Closing delay		80 ms
Breaking time		1000 ms
Number of operations per hour - max		60
Signal duration of remote operator at switch off - min		250 ms
Signal duration of remote operator at switch on - min		30 ms
<b>Technical Data - Mechanical</b>		
Switch drive type		Motor drive

Special features		Cannot be combined with switch-disconnector PN... M22-CK11(20/02) dual auxiliary switch cannot be combined with NZM3-XR... remote operator
Lifespan, mechanical		15000 operations
<b>Technical Data - Mechanical - Terminals</b>		
Terminal capacity (solid/flexible conductor)		18 - 14 AWG 0.75 mm <sup>2</sup> - 2.5 mm <sup>2</sup> with ferrule
<b>Design verification as per IEC/EN 61439</b>		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Motor operator for power circuit-breaker (EC001030)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Electrical drive for circuit breakers (ecl@ss13-27-37-04-12 [AKF010018])		
Type of switch drive		Motor drive
Rated control supply voltage AC 50 Hz	V	0 - 0
Rated control supply voltage AC 60 Hz	V	0 - 0
Rated control supply voltage DC	V	220 - 250
Voltage type for actuating		AC