



Fuse-link, LV, 25 A, AC 500 V, NH000, gL/gG, IEC, dual indicator, insulated gripping lugs



**25NHG000BI**

|                                      |  |   |
|--------------------------------------|--|---|
| Product name                         |  | Eaton Bussmann series low voltage NH Fuse   |
| Part no.                             |  | NH FUSE 25A 500V SIZE 000 GG IMGL   |
| EAN                                  |  | 5027590470988   |
| Product Length/Depth                 |  | 79 millimetre   |
| Product height                       |  | 51 millimetre   |
| Product width                        |  | 21 millimetre   |
| Product weight                       |  | 135 gram  |
| Compliances                          |  | CE Marked<br>RoHS Compliant   |
| Certifications                       |  | DIN 43620<br>IEC 60269-2<br>IEC 60269-1   |
| Product Tradename                    |  | None  |
| Product Type                         |  | Low voltage NH fuse   |
| Product Sub Type                     |  | None  |
| Amperage Rating                      |  | 25 A  |
| Voltage rating                       |  | 500 V   |
| Voltage type                         |  | AC  |
| Breaking capacity                    |  | 120 kA  |
| Class                                |  | Class gG/gL   |
| Fuse size                            |  | NH000   |
| Insulated metal gripping lugs (IMGL) |  | Yes   |
| Suitable for                         |  | Microswitch 170H0236<br>EBF Vertical fuse rail<br>EBV Vertical fuse switch-disconnectors<br>EBH Size 000 Horizontal fuse switch-disconnectors |

**Technical data ETIM 8.0**

|   |    |   |
|---|----|---|
| Circuit breakers and fuses (EG000020) / Knife blade fuse (EC000055)   |    |   |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) |    |   |
| Fuse construction type according to IEC 60269   |    | NH000   |
| Voltage type  |    | AC  |
| Rated current   | A  | 25  |
| Rated voltage AC  | V  | 500   |
| Rated voltage DC  | V  |   |
| Rated switching capacity  | kA | 120   |
| Utilization category  |    | gL/gG (cable protection/equipment protection) |
| Type of fuse status indicator   |    | Combination fuse status indicator             |
| Insulated metal gripping lugs (IMGL)  |    | Yes   |
| Power loss at rated current   | W  | 3.1   |