## Extension shaft, for max. mounting depth = 400mm



Part no. NZM1/2-XV4

261232

**EL Number** 4358731

(Norway)

| General specifications   |  |
|--|--|
| Product name   | Eaton Moeller series NZM operating element accessory   |
| Part no.   | NZM1/2-XV4   |
| EAN  | 4015082612320  |
| Product Length/Depth   | 290 millimetre   |
| Product height   | 12 millimetre  |
| Product width  | 12 millimetre  |
| Product weight   | 0.126 kilogram   |
| Compliances  | UL/CSA<br>IEC<br>RoHS conform  |
| Product Tradename  | NZM  |
| Product Type   | Accessories  |
| Product Sub Type   | Operating element accessory  |
| Delivery program   |  |
| Туре   | Accessory  |
| .,,,,  | Extension shaft  |
| Features   | 400 mm max. mounting depth   |
| Special features   | Length 290 mm, can be cut to desired length  |
| Frame  | NZM1/2   |
| Fitted with:   | Extension shaft, 1 pc.   |
| Used with  | NZM2(-4), PN2(-4), N(S)2(-4)<br>NZM1(-4), PN1(-4), N(S)1(-4)   |
| Technical Data - Mechanical  |  |
| Cross section height   | 8 mm   |
| Cross section width  | 8 mm   |
| Special features   | Length 290 mm, can be cut to desired length  |
| Design verification as per IEC/EN 61439  |  |
| 10.2.2 Corrosion resistance  | Meets the product standard's requirements.   |
| 10.2.3.1 Verification of thermal stability of enclosures                         | Meets the product standard's requirements.   |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat       | Meets the product standard's requirements.   |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | Meets the product standard's requirements.   |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                 | Meets the product standard's requirements.   |
| 10.2.5 Lifting   | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.6 Mechanical impact   | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.7 Inscriptions  | Meets the product standard's requirements.   |
| 10.3 Degree of protection of assemblies  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.4 Clearances and creepage distances   | Meets the product standard's requirements.   |
| 10.5 Protection against electric shock   | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.6 Incorporation of switching devices and components                           | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.7 Internal electrical circuits and connections                                | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors   | Is the panel builder's responsibility.   |
| 10.9.2 Power-frequency electric strength   | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage   | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material                         | Is the panel builder's responsibility.   |
| 10.10 Temperature rise   | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating   | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |

| 10.12 Electromagnetic compatibility | Is the panel builder's responsibility. The specifications for the switchgear must be observed.           |
|-------------------------------------|--|
| 10.13 Mechanical function           | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

## Technical data ETIM 9.0

| Low-voltage industrial components (EG000017) / Switch operating shaft (EC000916)   |    |     |  |  |
|--|----|-----|--|--|
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Switch axle (ecl@ss13-27-37-04-13 [AKF011018]) |    |     |  |  |
| Length   | mm | 290 |  |  |
| Cross section height   | mm | 8   |  |  |
| Cross section width  | mm | 8   |  |  |