## DATASHEET - XIOC-TERM30-CNT4

Plug for XIOC counter modules, 30pole, 4m



Part no. XIOC-TERM30-CNT4 262248 EL Number 4519647

(Norway)

General specifications	
Product name	Eaton XIOC Accessory Plug
Part no.	XIOC-TERM30-CNT4
EAN	4015082622480
Product Length/Depth	200 millimetre
Product height	25 millimetre
Product width	200 millimetre
Product weight	0.5 kilogram
Certifications	Request filed for UL and CSA
Product Tradename	XIOC
Product Type	Accessory
Product Sub Type	Plug
Catalog Notes	One 18 pole terminal plug is required for each digital and analog module as well as XC modular PLCs.
General information	
Used with	XIOC-2CNT-100KHZ XIOC-1CNT-100KHZ
Climatic environmental conditions	
Ambient operating temperature - min	0°0
Ambient operating temperature - max	55 °C
Design verification	
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	0 A
Static heat dissipation, non-current-dependent Pvs	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Meets the product standard's requirements.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## **Technical data ETIM 9.0**

Programmable logic controllers PLC (EG000024) / Accessories/spare parts for controls (EC002584)

Electric engineering, automation, process control engineering / Display and control component / Panel (HMI) / Panel (HMI, accessories) (ecl@ss13-27-33-02-92 [AFX005008])		
Type of electrical accessory/spare part	Plug	
Type of mechanical accessory/spare part	Other	
Accessory	Yes	
Spare part	No	