

Busbars, for SPC, 11HP



**Part no.**                      **ZV-KSBI-11TE**  
**263970**

<b>General specifications</b>		
Product name		Eaton Distribution parts
Part no.		ZV-KSBI-11TE
EAN		4015082639709
Product Length/Depth		194.2 millimetre
Product height		14.3 millimetre
Product width		14.9 millimetre
Product weight		0.054 kilogram
Compliances		RoHS conform
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
<b>Product Specification Details</b>		
Color		Other
Cross section		16 mm <sup>2</sup>
Electric connection type		Fork
Features		Insulated Can be cut to size
Number of modular spacings		11
Number of phases		1
Number of poles		Single-pole
Pitch dimensions		0 mm
Rated conditional short-circuit current (I <sub>q</sub> )		0 kA
Rated operational voltage (U <sub>e</sub> ) - max		400 V
Rated short-time withstand current (I <sub>cw</sub> )		0 kA
Rated surge voltage		0 kV
Rated uninterrupted current (I <sub>u</sub> )		0 A
Suitable for number of devices		12

**Technical data ETIM 9.0**

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss13-27-37-13-06 [ACN992016])		
Number of phases		1
Number of poles		1
Suitable for number of devices		12
Module width	mm	0
Cross section	mm <sup>2</sup>	16
Length	mm	194.2
Can be cut to size		Yes
Width in number of modular spacings		11
Rated permanent current I <sub>u</sub>	A	0
Type of electric connection		Fork
Insulated		Yes
Rated surge voltage	kV	0
Conditioned rated short-circuit current I <sub>q</sub>	kA	0

Max. rated operation voltage $U_e$	V	400
Rated short-time withstand current $I_{cw}$	kA	0
Suitable for devices with N-conductor		No
Suitable for devices with auxiliary switch		No
Colour		Other