DATASHEET - NZM1/2-XZB

Additional plate

Part no.

NZM1/2-XZB 266676



General specifications	
Product name	Eaton Moeller series NZM operating element accessory
Part no.	NZM1/2-XZB
EAN	4015082666767
Product Length/Depth	145 millimetre
Product height	3 millimetre
Product width	50 millimetre
Product weight	0.176 kilogram
Compliances	IEC UL/CSA RoHS conform
Product Tradename	NZM
Product Type	Accessories
Product Sub Type	Operating element accessory
Delivery program	
Туре	Accessory Additional plate
Features	For fitting to the mounting bracket when using N conductor or PE conductor terminals K25, K50, K95 or K150
Special features	Additional terminal arrangement for sidewall drive with mounting bracket For fitting to the mounting bracket when using N conductor or PE conductor terminals K50/1, K95/ or K150/
Frame	NZM1/2
Suitable for	Switch disconnector Power circuit breaker
Used with	NZM1-4 PN1 PN2-4 NZM1 NZM1-NA NZM2 NZM2-4 NS1 N2 N1-4 N2-4 NZM2-NA PN1-4 N1 NS2 PN2
Technical Data - Mechanical	
Color	Black
Degree of protection / NEMA enclosure type	IP66 Other
Special features	Additional terminal arrangement for sidewall drive with mounting bracket For fitting to the mounting bracket when using N conductor or PE conductor terminals K50/1, K95/ or K150/
Design verification as per IEC/EN 61439	
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.

10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Handle for power circuit breaker (EC000229)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Handle for switch devices (ecl@ss13-27-37-04-14 [AKF012019])		
With restart blockage	No	
With key lock	No	
Padlock locking	No	
Colour	Black	
Suitable for emergency stop	No	
With extension shaft	No	
Suitable for power circuit breaker	Yes	
Suitable for switch disconnector	Yes	
Degree of protection (NEMA)	Other	