

Connection, on rear, bottom 3p, size 3

**Part no.**                    **+NZM3-XKRU**  
**266791**

<b>General specifications</b>	
Product name	Eaton Moeller series NZM connection type
Part no.	+NZM3-XKRU
EAN	4015082667917
Product Length/Depth	160 millimetre
Product height	45 millimetre
Product width	65 millimetre
Product weight	0.832 kilogram
Compliances	UL/CSA IEC RoHS conform
Product Tradename	NZM
Product Type	Accessories
Product Sub Type	Connection type
<b>Delivery program</b>	
Type	Accessory Connection on rear Terminal
Number of poles	Three-pole
Amperage Rating	630 A (Cu), 500 A (Al)
Frame	NZM3
Suitable for	Copper cable lugs Three-pole Aluminum cable lug
Used with	NZM3, PN3, N3
<b>Technical Data - Mechanical</b>	
Mounting position	Fitted at the bottom
<b>Technical Data - Mechanical - Terminals</b>	
Terminal capacity (stranded cable)	16 mm <sup>2</sup> - 240 mm <sup>2</sup> (2x) 16 mm <sup>2</sup> - 240 mm <sup>2</sup> (1x)
Terminal capacity (copper busbar)	Max. 30 mm x 10 mm + 30 mm x 5 mm Min. 20 mm x 5 mm
Terminal capacity (copper strip)	6 segments of 16 mm x 0.8 mm - 10 segments of 32 mm x 1 mm + 5 segments of 32 mm x 1 mm
<b>Design verification as per IEC/EN 61439</b>	
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.

10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>Additional information</b>			
Model			Other

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Wiring set for power circuit breaker (EC002050)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Wiring set for circuit breaker (ecl@ss13-27-37-04-24 [ACN957016])			
Suitable for number of poles			3
Model			Other