



Part no.

EL Number  
(Norway)

EVG-2PHAS/4MODUL  
268220  
1657151

|   |  |  |
|---|--|--|
| General specifications                                    |  |  |
| Product name  |  | Eaton Moeller series busbar  |
| Part no.  |  | EVG-2PHAS/4MODUL   |
| EAN   |  | 4015082682200  |
| Product Length/Depth                                      |  | 27 millimetre  |
| Product height  |  | 8 millimetre   |
| Product width   |  | 65 millimetre  |
| Product weight  |  | 0.02 kilogram  |
| Compliances   |  | RoHS conform   |
| Product Tradename   |  | None   |
| Product Type  |  | Busbar   |
| Product Sub Type  |  | None   |
| Product Specification Details                             |  |  |
| Accessory/spare part type                                 |  | Busbar for combined residual current/power circuit breaker<br>Busbar for miniature circuit breaker<br>Busbar for residual current circuit breakers |
| Color   |  | Other  |
| Cross section   |  | 10 mm <sup>2</sup>   |
| EL number   |  | 1657151  |
| Electric connection type                                  |  | Fork   |
| Features  |  | Insulated  |
| Functions   |  | Busbar   |
| Number of modular spacings                                |  | 4  |
| Number of phases  |  | 2  |
| Number of poles   |  | Two-pole   |
| Pitch dimensions  |  | 0 mm   |
| Rated conditional short-circuit current (I <sub>q</sub> ) |  | 25 kA  |
| Rated operational voltage (U <sub>e</sub> ) - max         |  | 500 V  |
| Rated short-time withstand current (I <sub>cw</sub> )     |  | 0 kA   |
| Rated surge voltage                                       |  | 4 kV   |
| Rated uninterrupted current (I <sub>u</sub> )             |  | 63 A   |
| Suitable for  |  | 2 devices  |
| Suitable for number of devices                            |  | 2  |
| Type  |  | Busbar<br>EVG  |
| Used with   |  | Busbar<br>EVG  |

Technical data ETIM 9.0

|  |                 |    |
|--|-----------------|----|
| Low-voltage industrial components (EG000017) / Phase busbar (EC000215)   |                 |    |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecI@ss13-27-37-13-06 [ACN992016]) |                 |    |
| Number of phases   |                 | 2  |
| Number of poles  |                 | 2  |
| Suitable for number of devices   |                 | 2  |
| Module width   | mm              | 0  |
| Cross section  | mm <sup>2</sup> | 10 |
| Length   | mm              | 27 |
| Can be cut to size   |                 | No |
| Width in number of modular spacings  |                 | 4  |

|  |    |       |
|--|----|-------|
| Rated permanent current Iu                 | A  | 63    |
| Type of electric connection                |    | Fork  |
| Insulated                                  |    | Yes   |
| Rated surge voltage                        | kV | 4     |
| Conditioned rated short-circuit current Iq | kA | 25    |
| Max. rated operation voltage Ue            | V  | 500   |
| Rated short-time withstand current Icw     | kA | 0     |
| Suitable for devices with N-conductor      |    | No    |
| Suitable for devices with auxiliary switch |    | No    |
| Colour                                     |    | Other |