

Circuit-breaker, 3p, 200A



**Part no. NZMN2-A200-NA  
269227**

General specifications		
Product name		Eaton Moeller series NZM molded case circuit breaker thermo-magnetic
Part no.		NZMN2-A200-NA
EAN		4015082692278
Product Length/Depth		149 millimetre
Product height		195 millimetre
Product width		105 millimetre
Product weight		2.394 kilogram
Compliances		RoHS conform
Certifications		IEC CE marking UL/CSA CSA (File No. 22086) UL (Category Control Number DIVQ) Specially designed for North America CSA (Class No. 1432-01) UL 489 CSA-C22.2 No. 5-09 CSA certified IEC 60947-2 UL listed IEC/EN 60947 UL (File No. E31593)
Product Tradename		NZM
Product Type		Molded case circuit breaker
Product Sub Type		Thermo-magnetic
Delivery program		
Application		Branch circuits, feeder circuits Use in unearthed supply systems at 690 V
Type		Circuit breaker
Circuit breaker frame type		NZM2
Number of poles		Three-pole
Amperage Rating		200 A
Release system		Thermomagnetic release
Features		Protection unit Motor drive optional
Special features		Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I <sub>cn</sub> ) Rated current = rated uninterrupted current: 200 A Switches conform to UL/CSA as well as the IEC regulations. IEC switching performance values are contained on the rating plate. Adjustable overload releases I <sub>r</sub>
Technical Data - Electrical		
Voltage rating		690 V - 690 V
Rated operating voltage U <sub>e</sub> (UL) - max		600Y/347 V, 480 V
Rated insulation voltage (U <sub>i</sub> )		1000 V AC
Rated impulse withstand voltage (U <sub>imp</sub> ) at auxiliary contacts		6000 V
Rated impulse withstand voltage (U <sub>imp</sub> ) at main contacts		8000 V
Rated operational current		300 A (415 V AC-1, making and breaking capacity) 200 A (690 V AC-1, making and breaking capacity) 300 A (380/400 V AC-1, making and breaking capacity) 200 A (660-690 V AC-3, making and breaking capacity)
Rated short-time withstand current (t = 0.3 s)		1.9 kA
Rated short-time withstand current (t = 1 s)		1.9 kA
Instantaneous current setting (I <sub>i</sub> ) - min		1200 A
Instantaneous current setting (I <sub>i</sub> ) - max		2000 A
Overload current setting (I <sub>r</sub> ) - min		160 A

Overload current setting (I <sub>r</sub> ) - max		200 A
Short delay current setting (I <sub>sd</sub> ) - min		0 A
Short delay current setting (I <sub>sd</sub> ) - max		0 A
Short-circuit release non-delayed setting - min		1200 A
Short-circuit release non-delayed setting - max		2000 A
Rated short-circuit breaking capacity I <sub>cs</sub> (IEC/EN 60947) at 230 V, 50/60 Hz		85 kA
Rated short-circuit breaking capacity I <sub>cs</sub> (IEC/EN 60947) at 400/415 V, 50/60 Hz		50 kA
Rated short-circuit breaking capacity I <sub>cs</sub> (IEC/EN 60947) at 440 V, 50/60 Hz		35 kA
Rated short-circuit breaking capacity I <sub>cs</sub> (IEC/EN 60947) at 525 V, 50/60 Hz		25 kA
Rated short-circuit breaking capacity I <sub>cs</sub> (IEC/EN 60947) at 690 V, 50/60 Hz		5 kA
Rated short-circuit making capacity I <sub>cm</sub> at 240 V, 50/60 Hz		187 kA
Rated short-circuit making capacity I <sub>cm</sub> at 400/415 V, 50/60 Hz		105 kA
Rated short-circuit making capacity I <sub>cm</sub> at 440 V, 50/60 Hz		74 kA
Rated short-circuit making capacity I <sub>cm</sub> at 525 V, 50/60 Hz		53 kA
Rated short-circuit making capacity I <sub>cm</sub> at 690 V, 50/60 Hz		40 kA
Short-circuit total breaktime		< 10 ms
Low-voltage HBC fuse - max		355 A gG/gL
Electrical connection type of main circuit		Screw connection
Isolation		300 V AC (between the auxiliary contacts) 500 V AC (between auxiliary contacts and main contacts)
Number of operations per hour - max		120
Handle type		Rocker lever
Utilization category		A (IEC/EN 60947-2)
Overvoltage category		III
Pollution degree		3
Lifespan, electrical		6500 operations at 415 V AC-3 7500 operations at 690 V AC-1 10000 operations at 400 V AC-1 5000 operations at 690 V AC-3 6500 operations at 400 V AC-3
Direction of incoming supply		As required
<b>Technical Data - Mechanical</b>		
Mounting Method		Built-in device fixed built-in technique Fixed DIN rail (top hat rail) mounting optional
Degree of protection		IP20 (basic degree of protection, in the operating controls area) IP20
Degree of protection (IP), front side		IP40 (with insulating surround) IP66 (with door coupling rotary handle)
Degree of protection (terminations)		IP00 (terminations, phase isolator and strip terminal) IP10 (tunnel terminal)
Protection against direct contact		Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110
Shock resistance		20 g (half-sinusoidal shock 20 ms)
Number of auxiliary contacts (change-over contacts)		0
Number of auxiliary contacts (normally closed contacts)		0
Number of auxiliary contacts (normally open contacts)		0
Position of connection for main current circuit		Front side
Climatic proofing		Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Special features		Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I <sub>cn</sub> ) Rated current = rated uninterrupted current: 200 A Switches conform to UL/CSA as well as the IEC regulations. IEC switching performance values are contained on the rating plate. Adjustable overload releases I <sub>r</sub>
Lifespan, mechanical		20000 operations
<b>Technical Data - Mechanical - Terminals</b>		
Standard terminals		Screw terminal
Terminal capacity (control cable)		16 mm <sup>2</sup> - 18 mm <sup>2</sup> (2x) 14 mm <sup>2</sup> - 18 mm <sup>2</sup> (1x)
Terminal capacity (aluminum solid conductor/cable)		16 mm <sup>2</sup> (1x) at tunnel terminal
Terminal capacity (copper busbar)		M8 at rear-side screw connection

		Min. 16 mm x 5 mm direct at switch rear-side connection Max. 20 mm x 5 mm direct at switch rear-side connection
Terminal capacity (copper solid conductor/cable)		16 mm <sup>2</sup> (1x) at tunnel terminal 6 mm <sup>2</sup> - 11 mm <sup>2</sup> (1x) direct at switch rear-side connection 6 mm <sup>2</sup> - 12 mm <sup>2</sup> (1x) at box terminal
Terminal capacity (copper stranded conductor/cable)		4 mm <sup>2</sup> - 3/0 mm <sup>2</sup> (1x) direct at switch rear-side connection 4 mm <sup>2</sup> - 350 mm <sup>2</sup> (1x) at tunnel terminal 4 mm <sup>2</sup> - 350 mm <sup>2</sup> (1x) at box terminal
Terminal capacity (copper strip)		Max. 10 segments of 16 mm x 0.8 mm at rear-side connection (punched) Min. 2 segments of 16 mm x 0.8 mm at rear-side connection (punched) Max. 10 segments of 16 mm x 0.8 mm at box terminal Min. 2 segments of 9 mm x 0.8 mm at box terminal
<b>Design verification as per IEC/EN 61439 - technical data</b>		
Rated operational current for specified heat dissipation (In)		200 A
Equipment heat dissipation, current-dependent		48 W
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Ambient storage temperature - min		40 °C
Ambient storage temperature - max		70 °C
<b>Design verification as per IEC/EN 61439</b>		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>Additional information</b>		
Functions		Current limiting circuit breaker System and cable protection

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EC000228)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecl@ss13-27-37-04-09 [AJZ716018])		
Rated permanent current Iu	A	200
Rated voltage	V	690 - 690
Rated short-circuit breaking capacity Icu at 400 V, 50 Hz	kA	50
Overload release current setting	A	160 - 200
Adjustment range short-term delayed short-circuit release	A	0 - 0
Adjustment range undelayed short-circuit release	A	1200 - 2000
Power loss	W	48
Device construction		Built-in device fixed built-in technique

Integrated earth fault protection		No
Type of electrical connection of main circuit		Screw connection
Suitable for DIN rail (top hat rail) mounting		No
DIN rail (top hat rail) mounting optional		Yes
Number of auxiliary contacts as normally closed contact		0
Number of auxiliary contacts as normally open contact		0
Number of auxiliary contacts as change-over contact		0
With switched-off indicator		No
With integrated under voltage release		No
Number of poles		3
Position of connection for main current circuit		Front side
Type of control element		Rocker lever
Complete device with protection unit		Yes
Motor drive integrated		No
Motor drive optional		Yes
Degree of protection (IP)		IP20