

Busbars, np, angled blue, 16mm<sup>2</sup>



Part no. **Z-SV-16/1N-1TE/F**  
**269524**

General specifications		
Product name		Eaton Distribution parts
Part no.		Z-SV-16/1N-1TE/F
EAN		4015082695248
Product Length/Depth		19 millimetre
Product height		15 millimetre
Product width		1008 millimetre
Product weight		0.233 kilogram
Compliances		RoHS conform
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Color		Other
Cross section		16 mm <sup>2</sup>
Electric connection type		Pin
Features		Can be cut to size
Number of modular spacings		1
Number of phases		1
Number of poles		Two-pole
Pitch dimensions		0 mm
Rated conditional short-circuit current (I <sub>q</sub> )		0 kA
Rated operational voltage (U <sub>e</sub> ) - max		415 V
Rated short-time withstand current (I <sub>cw</sub> )		0 kA
Rated surge voltage		4 kV
Rated uninterrupted current (I <sub>u</sub> )		0 A
Suitable for number of devices		56

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecI@ss13-27-37-13-06 [ACN992016])		
Number of phases		1
Number of poles		2
Suitable for number of devices		56
Module width	mm	0
Cross section	mm <sup>2</sup>	16
Length	mm	19
Can be cut to size		Yes
Width in number of modular spacings		1
Rated permanent current I <sub>u</sub>	A	0
Type of electric connection		Pin
Insulated		No
Rated surge voltage	kV	4
Conditioned rated short-circuit current I <sub>q</sub>	kA	0
Max. rated operation voltage U <sub>e</sub>	V	415

Rated short-time withstand current I <sub>cw</sub>	kA	0
Suitable for devices with N-conductor		No
Suitable for devices with auxiliary switch		No
Colour		Other