





**Contactor, 3 pole, 380 V 400 V 3 kW, 1 N/O, 24 V 60 Hz, AC operation, Screw terminals**



**Part no. DILM7-10(24V60HZ)**  
**Catalog No. 276541**  
**Alternate Catalog No. XTCE007B10B6**

**Delivery program**

|   |                |    |  |  |
|---|----------------|----|--|--|
| Product range   |                |    |  | Contactors   |
| Application   |                |    |  | Contactors for Motors  |
| Subrange  |                |    |  | Contactors up to 170 A, 3 pole   |
| Utilization category                                      |                |    |  | AC-1: Non-inductive or slightly inductive loads, resistance furnaces<br>NAC-3: Normal AC induction motors: starting, switch off during running<br>AC-4: Normal AC induction motors: starting, plugging, reversing, inching |
| Notes   |                |    |  | <br>Also suitable for motors with efficiency class IE3.<br>IE3-ready devices are identified by the logo on their packaging.              |
| Connection technique                                      |                |    |  | Screw terminals  |
| Number of poles   |                |    |  | 3 pole   |
| <b>Rated operational current</b>                          |                |    |  |  |
| AC-3  |                |    |  |  |
| Notes   |                |    |  | At maximum permissible ambient temperature (open.)   |
| 380 V 400 V   | $I_e$          | A  |  | 7  |
| AC-1  |                |    |  |  |
| Conventional free air thermal current, 3 pole, 50 - 60 Hz |                |    |  |  |
| Open  |                |    |  |  |
| at 40 °C  | $I_{th} = I_e$ | A  |  | 22   |
| enclosed  | $I_{th}$       | A  |  | 18   |
| Conventional free air thermal current, 1 pole             |                |    |  |  |
| open  | $I_{th}$       | A  |  | 50   |
| enclosed  | $I_{th}$       | A  |  | 45   |
| <b>Max. rating for three-phase motors, 50 - 60 Hz</b>     |                |    |  |  |
| AC-3  |                |    |  |  |
| 220 V 230 V   | P              | kW |  | 2.2  |
| 380 V 400 V   | P              | kW |  | 3  |
| 660 V 690 V   | P              | kW |  | 3.5  |
| AC-4  |                |    |  |  |
| 220 V 230 V   | P              | kW |  | 1  |
| 380 V 400 V   | P              | kW |  | 2.2  |
| 660 V 690 V   | P              | kW |  | 2.9  |
| <b>Contacts</b>   |                |    |  |  |
| N/O = Normally open                                       |                |    |  | 1 N/O  |
| Contact sequence  |                |    |  |    |
| <b>Instructions</b>                                       |                |    |  |  |
| Can be combined with auxiliary contact                    |                |    |  | Contacts to EN 50 012.<br>DILM32-XHI..<br>DILA-XHI(V)..  |
| Actuating voltage   |                |    |  | 24 V 60 Hz   |
| Voltage AC/DC   |                |    |  | AC operation   |
| Connection to SmartWire-DT                                |                |    |  | no   |

## Technical data

### General

|   |                 |               |  |
|---|-----------------|---------------|--|
| Standards   |                 |               | IEC/EN 60947, VDE 0660, UL, CSA  |
| Lifespan, mechanical  |                 |               |  |
| AC operated   | Operations      | $\times 10^6$ | 10   |
| Operating frequency, mechanical                                       |                 |               |  |
| AC operated   | Operations/h    |               | 9000   |
| Climatic proofing   |                 |               | Damp heat, constant, to IEC 60068-2-78<br>Damp heat, cyclic, to IEC 60068-2-30     |
| Ambient temperature   |                 |               |  |
| Open  | °C              |               | -25 - +60  |
| Enclosed  | °C              |               | - 25 - 40  |
| Storage   | °C              |               | - 40 - 80  |
| Mounting position   |                 |               |  |
| Mechanical shock resistance (IEC/EN 60068-2-27)                       |                 |               |  |
| Half-sinusoidal shock, 10 ms  |                 |               |  |
| Main contacts   |                 |               |  |
| N/O contact   | g               |               | 10   |
| Auxiliary contacts  |                 |               |  |
| N/O contact   | g               |               | 7  |
| N/C contact   | g               |               | 5  |
| Mechanical shock resistance (IEC/EN 60068-2-27) when tabletop-mounted |                 |               |  |
| Half-sinusoidal shock, 10 ms  |                 |               |  |
| Main contacts   |                 |               |  |
| N/O contact   | g               |               | 5.7  |
| Auxiliary contacts  |                 |               |  |
| N/O contact   | g               |               | 3.4  |
| N/C contact   | g               |               | 3.4  |
| Degree of Protection  |                 |               | IP20   |
| Protection against direct contact when actuated from front (EN 50274) |                 |               | Finger and back-of-hand proof  |
| Altitude  | m               |               | Max. 2000  |
| Weight  |                 |               |  |
| AC operated   | kg              |               | 0.24   |
| Screw connector terminals   |                 |               |  |
| Terminal capacity main cable  |                 |               |  |
| Solid   | mm <sup>2</sup> |               | 1 x (0.75 - 4)<br>2 x (0.75 - 2.5)   |
| Flexible with ferrule   | mm <sup>2</sup> |               | 1 x (0.75 - 2.5)<br>2 x (0.75 - 2.5)   |
| Solid or stranded   | AWG             |               | single 18 - 10, double 18 - 14   |
| Stripping length  | mm              |               | 10   |
| Terminal screw  |                 |               | M3.5   |
| Tightening torque   | Nm              |               | 1.2  |
| Tool  |                 |               |  |
| Pozidriv screwdriver  | Size            |               | 2  |
| Standard screwdriver  | mm              |               | 0.8 x 5.5<br>1 x 6   |
| Terminal capacity control circuit cables                              |                 |               |  |
| Solid   | mm <sup>2</sup> |               | 1 x (0.75 - 4)<br>2 x (0.75 - 2.5)   |
| Flexible with ferrule   | mm <sup>2</sup> |               | 1 x (0.75 - 2.5)<br>2 x (0.75 - 2.5)   |
| Solid or stranded   | AWG             |               | 18 - 14  |

|                      |  |      |                    |
|----------------------|--|------|--------------------|
| Stripping length     |  | mm   | 10                 |
| Terminal screw       |  |      | M3.5               |
| Tightening torque    |  | Nm   | 1.2                |
| Tool                 |  |      |                    |
| Pozidriv screwdriver |  | Size | 2                  |
| Standard screwdriver |  | mm   | 0.8 x 5.5<br>1 x 6 |

### Main conducting paths

|  |             |      |       |
|--|-------------|------|-------|
| Rated impulse withstand voltage        | $U_{imp}$   | V AC | 8000  |
| Overvoltage category/pollution degree  |             |      | III/3 |
| Rated insulation voltage               | $U_i$       | V AC | 690   |
| Rated operational voltage              | $U_e$       | V AC | 690   |
| Safe isolation to EN 61140             |             |      |       |
| between coil and contacts              |             | V AC | 400   |
| between the contacts                   |             | V AC | 400   |
| Making capacity (p.f. to IEC/EN 60947) |             |      |       |
|  | Up to 690 V | A    | 112   |
| Breaking capacity                      |             |      |       |
| 220 V 230 V                            |             | A    | 70    |
| 380 V 400 V                            |             | A    | 70    |
| 500 V                                  |             | A    | 50    |
| 660 V 690 V                            |             | A    | 40    |
| Short-circuit rating                   |             |      |       |
| Short-circuit protection maximum fuse  |             |      |       |
| Type "2" coordination                  |             |      |       |
| 400 V                                  | gG/gL 500 V | A    | 20    |
| 690 V                                  | gG/gL 690 V | A    | 16    |
| Type "1" coordination                  |             |      |       |
| 400 V                                  | gG/gL 500 V | A    | 35    |
| 690 V                                  | gG/gL 690 V | A    | 20    |

### AC

|   |                |   |  |
|---|----------------|---|--|
| AC-1  |                |   |  |
| Rated operational current                                 |                |   |  |
| Conventional free air thermal current, 3 pole, 50 - 60 Hz |                |   |  |
| Open  |                |   |  |
| at 40 °C  | $I_{th} = I_e$ | A | 22   |
| at 50 °C  | $I_{th} = I_e$ | A | 21   |
| at 55 °C  | $I_{th} = I_e$ | A | 21   |
| at 60 °C  | $I_{th} = I_e$ | A | 20   |
| enclosed  | $I_{th}$       | A | 18   |
| Conventional free air thermal current, 1 pole             |                |   |  |
| open  | $I_{th}$       | A | 50   |
| enclosed  | $I_{th}$       | A | 45   |
| AC-3  |                |   |  |
| Rated operational current                                 |                |   |  |
| Open, 3-pole: 50 – 60 Hz                                  |                |   |  |
| Notes   |                |   | At maximum permissible ambient temperature (open.) |
| 220 V 230 V   | $I_e$          | A | 7  |
| 240 V   | $I_e$          | A | 7  |
| 380 V 400 V   | $I_e$          | A | 7  |
| 415 V   | $I_e$          | A | 7  |
| 440V  | $I_e$          | A | 7  |
| 500 V   | $I_e$          | A | 5  |
| 660 V 690 V   | $I_e$          | A | 4  |
| 380 V 400 V   | $I_e$          | A | 7  |

|              |   |     |     |
|--------------|---|-----|-----|
| Motor rating | P | kWh |     |
| 220 V 230 V  | P | kW  | 2.2 |
| 240V         | P | kW  | 2.2 |
| 380 V 400 V  | P | kW  | 3   |
| 415 V        | P | kW  | 4   |
| 440 V        | P | kW  | 4.5 |
| 500 V        | P | kW  | 3.5 |
| 660 V 690 V  | P | kW  | 3.5 |

#### AC-4

|                          |                |   |     |
|--------------------------|----------------|---|-----|
| Open, 3-pole: 50 – 60 Hz |                |   |     |
| 220 V 230 V              | I <sub>e</sub> | A | 5   |
| 240 V                    | I <sub>e</sub> | A | 5   |
| 380 V 400 V              | I <sub>e</sub> | A | 5   |
| 415 V                    | I <sub>e</sub> | A | 5   |
| 440 V                    | I <sub>e</sub> | A | 5   |
| 500 V                    | I <sub>e</sub> | A | 4.5 |
| 660 V 690 V              | I <sub>e</sub> | A | 4   |

|              |   |     |     |
|--------------|---|-----|-----|
| Motor rating | P | kWh |     |
| 220 V 230 V  | P | kW  | 1   |
| 240 V        | P | kW  | 1.5 |
| 380 V 400 V  | P | kW  | 2.2 |
| 415 V        | P | kW  | 2.3 |
| 440 V        | P | kW  | 2.4 |
| 500 V        | P | kW  | 2.5 |
| 660 V 690 V  | P | kW  | 2.9 |

#### DC

|                                 |                |   |    |
|---------------------------------|----------------|---|----|
| Rated operational current, open |                |   |    |
| DC-1                            |                |   |    |
| 60 V                            | I <sub>e</sub> | A | 20 |
| 110 V                           | I <sub>e</sub> | A | 20 |
| 220 V                           | I <sub>e</sub> | A | 15 |

#### Current heat loss

|   |  |    |     |
|---|--|----|-----|
| 3 pole, at I <sub>th</sub> (60°)                  |  | W  | 2.4 |
| Current heat loss at I <sub>e</sub> to AC-3/400 V |  | W  | 0.3 |
| Impedance per pole                                |  | mΩ | 2.5 |

#### Magnet systems

|  |          |                  |           |
|--|----------|------------------|-----------|
| Voltage tolerance  |          |                  |           |
| AC operated  | Pick-up  | x U <sub>c</sub> | 0.8 - 1.1 |
| Drop-out voltage AC operated   | Drop-out | x U <sub>c</sub> | 0.3 - 0.6 |
| Power consumption of the coil in a cold state and 1.0 x U <sub>S</sub> |          |                  |           |
| 50 Hz  | Pick-up  | VA               | 24        |
| 50 Hz  | Sealing  | VA               | 3.4       |
| 50 Hz  | Sealing  | W                | 1.4       |
| 60 Hz  | Pick-up  | VA               | 30        |
| 60 Hz  | Sealing  | VA               | 4.4       |
| 60 Hz  | Sealing  | W                | 1.4       |
| Duty factor  |          | % DF             | 100       |
| Changeover time at 100 % U <sub>S</sub> (recommended value)            |          |                  |           |
| Main contacts  |          |                  |           |
| AC operated  |          |                  |           |
| Closing delay  |          | ms               | 15 - 21   |
| Opening delay  |          | ms               | 9 - 18    |
| Arcing time  |          | ms               | 10        |

#### Electromagnetic compatibility (EMC)

|                      |  |  |               |
|----------------------|--|--|---------------|
| Emitted interference |  |  | to EN 60947-1 |
|----------------------|--|--|---------------|

**Rating data for approved types**

|   |    |                         |  |
|---|----|-------------------------|--|
| Switching capacity  |    |                         |  |
| Maximum motor rating                                      |    |                         |  |
| Three-phase   |    |                         |  |
| 200 V<br>208 V  | HP | 1.5                     |  |
| 230 V<br>240 V  | HP | 2                       |  |
| 460 V<br>480 V  | HP | 3                       |  |
| 575 V<br>600 V  | HP | 5                       |  |
| Single-phase  |    |                         |  |
| 115 V<br>120 V  | HP | 0.25                    |  |
| 230 V<br>240 V  | HP | 1                       |  |
| General use   | A  | 20                      |  |
| Auxiliary contacts  |    |                         |  |
| Pilot Duty  |    |                         |  |
| AC operated   |    | A600                    |  |
| DC operated   |    | P300                    |  |
| General Use   |    |                         |  |
| AC  | V  | 600                     |  |
| AC  | A  | 10                      |  |
| DC  | V  | 250                     |  |
| DC  | A  | 1                       |  |
| Short Circuit Current Rating                              |    |                         |  |
| SCCR  |    |                         |  |
| Basic Rating  |    |                         |  |
| SCCR  | kA | 5                       |  |
| max. Fuse   | A  | 45                      |  |
| max. CB   | A  | 60                      |  |
| 480 V High Fault  |    |                         |  |
| SCCR (fuse)   | kA | 30/100                  |  |
| max. Fuse   | A  | 25 Class RK5/20 Class J |  |
| SCCR (CB)   | kA | 65                      |  |
| max. CB   | A  | 16                      |  |
| 600 V High Fault  |    |                         |  |
| SCCR (fuse)   | kA | 30/100                  |  |
| max. Fuse   | A  | 25 Class RK5/20 Class J |  |
| Special Purpose Ratings                                   |    |                         |  |
| Electrical Discharge Lamps (Ballast)                      |    |                         |  |
| 480V 60Hz 3phase, 277V 60Hz 1phase                        | A  | 12                      |  |
| 600V 60Hz 3phase, 347V 60Hz 1phase                        | A  | 12                      |  |
| Incandescent Lamps (Tungsten)                             |    |                         |  |
| 480V 60Hz 3phase, 277V 60Hz 1phase                        | A  | 14                      |  |
| 600V 60Hz 3phase, 347V 60Hz 1phase                        | A  | 14                      |  |
| Resistance Air Heating                                    |    |                         |  |
| 480V 60Hz 3phase, 277V 60Hz 1phase                        | A  | 12                      |  |
| 600V 60Hz 3phase, 347V 60Hz 1phase                        | A  | 12                      |  |
| Refrigeration Control (CSA only)                          |    |                         |  |
| LRA 480V 60Hz 3phase                                      | A  | 60                      |  |
| FLA 480V 60Hz 3phase                                      | A  | 10                      |  |
| LRA 600V 60Hz 3phase                                      | A  | 60                      |  |
| FLA 600V 60Hz 3phase                                      | A  | 10                      |  |
| Definite Purpose Ratings (100,000 cycles acc. to UL 1995) |    |                         |  |
| LRA 480V 60Hz 3phase                                      | A  | 42                      |  |

|                      |    |      |
|----------------------|----|------|
| FLA 480V 60Hz 3phase | A  | 7    |
| Elevator Control     |    |      |
| 200V 60Hz 3phase     | HP | 0.75 |
| 200V 60Hz 3phase     | A  | 3.7  |
| 240V 60Hz 3phase     | HP | 1.5  |
| 240V 60Hz 3phase     | A  | 6    |
| 480V 60Hz 3phase     | HP | 2    |
| 480V 60Hz 3phase     | A  | 3.4  |
| 600V 60Hz 3phase     | HP | 3    |
| 600V 60Hz 3phase     | A  | 3.9  |

## Design verification as per IEC/EN 61439

|  |            |    |  |
|--|------------|----|--|
| Technical data for design verification   |            |    |  |
| Rated operational current for specified heat dissipation   | $I_n$      | A  | 7  |
| Heat dissipation per pole, current-dependent   | $P_{vid}$  | W  | 0.1  |
| Equipment heat dissipation, current-dependent  | $P_{vid}$  | W  | 0  |
| Static heat dissipation, non-current-dependent   | $P_{vs}$   | W  | 1.4  |
| Heat dissipation capacity  | $P_{diss}$ | W  | 0  |
| Operating ambient temperature min.   |            | °C | -25  |
| Operating ambient temperature max.   |            | °C | 60   |
| IEC/EN 61439 design verification   |            |    |  |
| 10.2 Strength of materials and parts   |            |    |  |
| 10.2.2 Corrosion resistance  |            |    |  |
|  |            |    | Meets the product standard's requirements.   |
| 10.2.3.1 Verification of thermal stability of enclosures   |            |    |  |
|  |            |    | Meets the product standard's requirements.   |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat   |            |    |  |
|  |            |    | Meets the product standard's requirements.   |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects |            |    |  |
|  |            |    | Meets the product standard's requirements.   |
| 10.2.4 Resistance to ultra-violet (UV) radiation   |            |    |  |
|  |            |    | Meets the product standard's requirements.   |
| 10.2.5 Lifting   |            |    |  |
|  |            |    | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.6 Mechanical impact   |            |    |  |
|  |            |    | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.7 Inscriptions  |            |    |  |
|  |            |    | Meets the product standard's requirements.   |
| 10.3 Degree of protection of ASSEMBLIES  |            |    |  |
|  |            |    | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.4 Clearances and creepage distances   |            |    |  |
|  |            |    | Meets the product standard's requirements.   |
| 10.5 Protection against electric shock   |            |    |  |
|  |            |    | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.6 Incorporation of switching devices and components   |            |    |  |
|  |            |    | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.7 Internal electrical circuits and connections  |            |    |  |
|  |            |    | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors   |            |    |  |
|  |            |    | Is the panel builder's responsibility.   |
| 10.9 Insulation properties   |            |    |  |
| 10.9.2 Power-frequency electric strength   |            |    |  |
|  |            |    | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage   |            |    |  |
|  |            |    | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material   |            |    |  |
|  |            |    | Is the panel builder's responsibility.   |
| 10.10 Temperature rise   |            |    |  |
|  |            |    | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating   |            |    |  |
|  |            |    | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.12 Electromagnetic compatibility  |            |    |  |
|  |            |    | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.13 Mechanical function  |            |    |  |
|  |            |    | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |

## Technical data ETIM 7.0

|   |   |         |
|---|---|---------|
| Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)   |   |         |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss10.0.1-27-37-10-03 [AAB718015]) |   |         |
| Rated control supply voltage $U_s$ at AC 50HZ   | V | 0 - 0   |
| Rated control supply voltage $U_s$ at AC 60HZ   | V | 24 - 24 |
| Rated control supply voltage $U_s$ at DC  | V | 0 - 0   |
| Voltage type for actuating  |   | AC      |

|   |    |                  |
|---|----|------------------|
| Rated operation current Ie at AC-1, 400 V               | A  | 22               |
| Rated operation current Ie at AC-3, 400 V               | A  | 7                |
| Rated operation power at AC-3, 400 V                    | kW | 3                |
| Rated operation current Ie at AC-4, 400 V               | A  | 5                |
| Rated operation power at AC-4, 400 V                    | kW | 2.2              |
| Rated operation power NEMA                              | kW | 2.2              |
| Modular version   |    | No               |
| Number of auxiliary contacts as normally open contact   |    | 1                |
| Number of auxiliary contacts as normally closed contact |    | 0                |
| Type of electrical connection of main circuit           |    | Screw connection |
| Number of normally closed contacts as main contact      |    | 0                |
| Number of main contacts as normally open contact        |    | 3                |

## Approvals

|                                      |  |   |
|--------------------------------------|--|---|
| Product Standards                    |  | IEC/EN 60947-4-1; UL 508; CSA-C22.2 No. 14-05; CE marking |
| UL File No.                          |  | E29096  |
| UL Category Control No.              |  | NLDX  |
| CSA File No.                         |  | 012528  |
| CSA Class No.                        |  | 2411-03, 3211-04  |
| North America Certification          |  | UL listed, CSA certified                                  |
| Specially designed for North America |  | No  |



- 1: Overload relay
- 2: Suppressor
- 3: Auxiliary contact modules





- Squirrel-cage motor
- Operating characteristics
- Starting: from rest
- Stopping: after attaining full running speed
- Electrical characteristics
- Make: up to 6 x rated motor current
- Break: up to 1 x rated motor current
- Utilization category
- 100 % AC-3
- Typical applications
- Compressors
- Lifts
- Mixers
- Pumps
- Escalators
- Agitators
- Fans
- Conveyor belts
- Centrifuges
- Hinged flaps
- Bucket-elevators
- Air conditioning system
- General drives in manufacturing and processing machines



- Extreme switching duty
- Squirrel-cage motor
- Operating characteristics
- Inching, plugging, reversing
- Electrical characteristics
- Make: up to 6 x rated motor current
- Break: up to 6 x rated motor current
- Utilization category
- 100 % AC-4
- Typical applications
- Printing presses
- Wire-drawing machines
- Centrifuges
- Special drives for manufacturing and processing machines



Switching conditions for non-motor consumers, 3 pole, 4 pole  
 Operating characteristics  
 Non inductive and slightly inductive loads  
 Electrical characteristics  
 Switch on: 1 x rated operational current  
 Switch off: 1 x rated operational current  
 Utilization category  
 100 % AC-1  
 Typical examples of application  
 Electric heat

## Dimensions



Contactor with auxiliary contact module DILM32-XHI.../DILA-XHI...



Contactor with auxiliary contact module DILA-XHIT...



DILM7...DILM15  
 DILA...  
 Contactor with auxiliary contact module

### Assets (links)

[Declaration of CE Conformity](#)

00002875

[Instruction Leaflets](#)

IL03407013Z2018\_07

### Additional product information (links)

**IL03407013Z (AWA2100-2126) Contactors**

IL03407013Z (AWA2100-2126) Contactors

[ftp://ftp.moeller.net/DOCUMENTATION/AWA\\_INSTRUCTIONS/IL03407013Z2020\\_05.pdf](ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL03407013Z2020_05.pdf)

Motor starters and "Special Purpose Ratings" for the North American market

[http://www.eaton.eu/ecm/groups/public/@pub/@europe/@electrical/documents/content/pct\\_3258146.pdf](http://www.eaton.eu/ecm/groups/public/@pub/@europe/@electrical/documents/content/pct_3258146.pdf)

|  |   |
|--|---|
| Switchgear of Power Factor Correction Systems  | <a href="http://www.moeller.net/binary/ver_techpapers/ver934en.pdf">http://www.moeller.net/binary/ver_techpapers/ver934en.pdf</a> |
| X-Start - Modern Switching Installations Efficiently Fitted and Wired Securely                 | <a href="http://www.moeller.net/binary/ver_techpapers/ver938en.pdf">http://www.moeller.net/binary/ver_techpapers/ver938en.pdf</a> |
| Mirror Contacts for Highly-Reliable Information Relating to Safety-Related Control Functions   | <a href="http://www.moeller.net/binary/ver_techpapers/ver944en.pdf">http://www.moeller.net/binary/ver_techpapers/ver944en.pdf</a> |
| Effect of the Cabel Capacitance of Long Control Cables on the Actuation of Contactors          | <a href="http://www.moeller.net/binary/ver_techpapers/ver949en.pdf">http://www.moeller.net/binary/ver_techpapers/ver949en.pdf</a> |
| Switchgear for Luminaires  | <a href="http://www.moeller.net/binary/ver_techpapers/ver955en.pdf">http://www.moeller.net/binary/ver_techpapers/ver955en.pdf</a> |
| Standard Compliant and Functionally Safe Engineering Design with Mechanical Auxiliary Contacts | <a href="http://www.moeller.net/binary/ver_techpapers/ver956en.pdf">http://www.moeller.net/binary/ver_techpapers/ver956en.pdf</a> |
| The Interaction of Contactors with PLCs  | <a href="http://www.moeller.net/binary/ver_techpapers/ver957en.pdf">http://www.moeller.net/binary/ver_techpapers/ver957en.pdf</a> |
| Busbar Component Adapters for modern Industrial control panels                                 | <a href="http://www.moeller.net/binary/ver_techpapers/ver960en.pdf">http://www.moeller.net/binary/ver_techpapers/ver960en.pdf</a> |