

## Miniature circuit breaker (MCB), 40 A, 4p, characteristic: C

**Part no.** FAZ-C40/4  
**279065**

**EL Number**  
**(Norway)** 1695198

| General specifications  |  |  |
|---|--|--|
| Product name  |  | Eaton Moeller series xEffect - FAZ MCB   |
| Part no.  |  | FAZ-C40/4  |
| EAN   |  | 4015082790653  |
| Product Length/Depth  |  | 80 millimetre  |
| Product height  |  | 75.5 millimetre  |
| Product width   |  | 72 millimetre  |
| Product weight  |  | 0.467 kilogram   |
| Compliances   |  | RoHS conform   |
| Certifications  |  | IEC/EN 60898<br>IEC/EN 60947-2<br>IEC 61373<br>EN45545-2   |
| Product Tradename   |  | xEffect - FAZ  |
| Product Type  |  | MCB  |
| Product Sub Type  |  | None   |
| Delivery program  |  |  |
| Application   |  | Switchgear for industrial and advanced commercial applications<br>xEffect - Switchgear for industrial and advanced commercial applications |
| Number of poles   |  | Four-pole  |
| Number of poles (total)   |  | 4  |
| Number of poles (protected)                                     |  | 4  |
| Tripping characteristic   |  | C  |
| Release characteristic  |  | C  |
| Amperage Rating   |  | 40 A   |
| Type  |  | FAZ<br>Miniature circuit breaker   |
| Technical Data - Electrical                                     |  |  |
| Voltage type  |  | AC   |
| Voltage rating  |  | 240 V AC / 415 V AC  |
| Voltage rating at DC  |  | 60 V DC (per pole)   |
| Voltage rating (IEC/EN 60898-1)                                 |  | 415 V AC   |
| Voltage rating (UL)   |  | 480Y/277 V   |
| Rated operational voltage (Ue) - max                            |  | 400 V  |
| Operational voltage (IEC/EN 60947-2) - max                      |  | 440 V AC   |
| Rated insulation voltage (Ui)                                   |  | 440 V  |
| Rated impulse withstand voltage (Uimp)                          |  | 4 kV   |
| Frequency rating - min  |  | 50 Hz  |
| Frequency rating - max  |  | 60 Hz  |
| Rated switching capacity (IEC/EN 60947-2) at max voltage rating |  | 10 kA  |
| Rated switching capacity (IEC/EN 60947-2)                       |  | 15 kA  |
| Rated switching capacity (IEC/EN 60898-1)                       |  | 10 kA  |
| Operational switching capacity                                  |  | 7.5 kA   |
| Breaking capacity   |  | 5 kA (UL1077)  |
| Rated service short-circuit breaking capacity (IEC/EN 60898-1)  |  | 7.5 kA   |
| Rated service short-circuit breaking capacity (IEC/EN 60947-2)  |  | 7.5 kA   |
| Rated short-circuit breaking capacity (EN 60898) at 230 V       |  | 10 kA  |
| Rated short-circuit breaking capacity (EN 60898) at 400 V       |  | 10 kA  |
| Rated short-circuit breaking capacity (IEC 60947-2) at 230 V    |  | 15 kA  |
| Rated short-circuit breaking capacity (IEC 60947-2) at 400 V    |  | 15 kA  |

|  |  |  |
|--|--|--|
| Admissible back-up fuse - max  |  | 125 A gL/gG  |
| Selectivity class  |  | 3  |
| Lifespan, electrical   |  | 10000 operations   |
| Overvoltage category   |  | III  |
| Pollution degree   |  | 2  |
| Direction of incoming supply   |  | As required  |
| <b>Technical Data - Mechanical</b>   |  |  |
| Frame  |  | 45 mm  |
| Enclosure width  |  | 80 mm  |
| Width in number of modular spacings  |  | 4  |
| Built-in depth   |  | 70.5 mm  |
| Mounting width per pole  |  | 17.5 mm  |
| Mounting width   |  | 17.5 mm  |
| Mounting Method  |  | Top-hat rail IEC/EN 60715  |
| Mounting position  |  | As required  |
| Degree of protection   |  | IP40 (when fitted)<br>IP20   |
| Terminals (top and bottom)   |  | Twin-purpose terminals   |
| Connectable conductor cross section (solid-core) - min                           |  | 1 mm <sup>2</sup>  |
| Connectable conductor cross section (solid-core) - max                           |  | 25 mm <sup>2</sup>   |
| Connectable conductor cross section (multi-wired) - min                          |  | 1 mm <sup>2</sup>  |
| Connectable conductor cross section (multi-wired) - max                          |  | 25 mm <sup>2</sup>   |
| Terminal capacity of screw terminals for main cable                              |  | 10 mm <sup>2</sup> (2x)  |
| Terminal capacity (control cable)  |  | 25 mm <sup>2</sup> (1x)  |
| Terminal protection  |  | Finger and hand touch safe, DGUV VS3, EN 50274   |
| Busbar material thickness  |  | 0.8 mm - 2 mm  |
| <b>Design verification as per IEC/EN 61439 - technical data</b>                  |  |  |
| Rated operational current for specified heat dissipation (In)                    |  | 40 A   |
| Heat dissipation per pole, current-dependent                                     |  | 0 W  |
| Equipment heat dissipation, current-dependent                                    |  | 13.6 W   |
| Static heat dissipation, non-current-dependent                                   |  | 0 W  |
| Heat dissipation capacity  |  | 0 W  |
| Ambient operating temperature - min  |  | -25 °C   |
| Ambient operating temperature - max  |  | 75 °C  |
| <b>Design verification as per IEC/EN 61439</b>                                   |  |  |
| 10.2.2 Corrosion resistance  |  | Meets the product standard's requirements.   |
| 10.2.3.1 Verification of thermal stability of enclosures                         |  | Meets the product standard's requirements.   |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat       |  | Meets the product standard's requirements.   |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects |  | Meets the product standard's requirements.   |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                 |  | Meets the product standard's requirements.   |
| 10.2.5 Lifting   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.6 Mechanical impact   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.7 Inscriptions  |  | Meets the product standard's requirements.   |
| 10.3 Degree of protection of assemblies  |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.4 Clearances and creepage distances   |  | Meets the product standard's requirements.   |
| 10.5 Protection against electric shock   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.6 Incorporation of switching devices and components                           |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.7 Internal electrical circuits and connections                                |  | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors   |  | Is the panel builder's responsibility.   |
| 10.9.2 Power-frequency electric strength   |  | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage   |  | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material                         |  | Is the panel builder's responsibility.   |
| 10.10 Temperature rise   |  | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating   |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |

|                                     |  |   |
|-------------------------------------|--|---|
| 10.12 Electromagnetic compatibility |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.            |
| 10.13 Mechanical function           |  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.  |
| <b>Additional information</b>       |  |   |
| Current limiting class              |  | 3   |
| Features                            |  | Additional equipment possible<br>Concurrently switching N-neutral   |
| Special features                    |  | Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity |
| Used with                           |  | Miniature circuit breaker<br>FAZ  |

## Technical data ETIM 9.0

|   |                 |          |
|---|-----------------|----------|
| Circuit breakers and fuses (EG000020) / Miniature circuit breaker (MCB) (EC000042)  |                 |          |
| Electric engineering, automation, process control engineering / Electrical installation, device / Miniature circuit breaker system (MCB) / Miniature circuit breaker (MCB) (ecl@ss13-27-14-19-01 [AAB905019]) |                 |          |
| Built-in depth  | mm              | 70.5     |
| Release characteristic  |                 | C        |
| Number of poles (total)   |                 | 4        |
| Number of protected poles   |                 | 4        |
| Rated current   | A               | 40       |
| Rated voltage   | V               | 400      |
| Rated insulation voltage $U_i$  | V               | 440      |
| Rated impulse withstand voltage $U_{imp}$   | kV              | 4        |
| Rated short-circuit breaking capacity $I_{cn}$ according to EN 60898 at 230 V   | kA              | 10       |
| Voltage type  |                 | AC       |
| Rated short-circuit breaking capacity $I_{cn}$ according to EN 60898 at 400 V   | kA              | 10       |
| Rated short-circuit breaking capacity $I_{cu}$ according to IEC 60947-2 at 230 V  | kA              | 15       |
| Rated short-circuit breaking capacity $I_{cu}$ according to IEC 60947-2 at 400 V  | kA              | 15       |
| Frequency   | Hz              | 50 - 60  |
| Power loss  | W               | 11.5     |
| Current limiting class  |                 | 3        |
| Flush-mounted installation  |                 | No       |
| Concurrently switching neutral conductor  |                 | Yes      |
| Over voltage category   |                 | 3        |
| Pollution degree  |                 | 2        |
| Additional equipment possible   |                 | Yes      |
| Width in number of modular spacings   |                 | 4        |
| Degree of protection (IP)   |                 | IP20     |
| Ambient temperature during operating  | °C              | -25 - 75 |
| Connectable conductor cross section multi-wired   | mm <sup>2</sup> | 1 - 25   |
| Connectable conductor cross section solid-core  | mm <sup>2</sup> | 1 - 25   |
| Explosion-proof   |                 | No       |