DATASHEET - ZAV-P5

Shaft extension, for P5, L=480mm

| Part no. | ZAV-P5 |
|-----------|---------|
| | 280979 |
| EL Number | 1417199 |
| (Norway) | |



| General specifications | |
|--|--|
| Product name | Eaton Moeller® series ZAV Accessory Shaft extension |
| Part no. | ZAV-P5 |
| EAN | 4015082809799 |
| Product Length/Depth | 25 millimetre |
| Product height | 480 millimetre |
| Product width | 25 millimetre |
| Product weight | 0.003 kilogram |
| Compliances | Contact Manufacturer |
| Certifications | UL/CSA certification not required |
| Product Tradename | ZAV |
| Product Type | Accessory |
| Product Sub Type | Shaft extension |
| Features & Functions | |
| Material | Aluminium |
| General information | |
| Shaft length | 480 mm |
| Туре | Shaft extension |
| Used with | P5 P5/V and P5/Z |
| Climatic environmental conditions | |
| Ambient operating temperature - min | -25 °C |
| Ambient operating temperature - max | 50 °C |
| Design verification | |
| Equipment heat dissipation, current-dependent Pvid | 0 W |
| Heat dissipation capacity Pdiss | 0 W |
| Heat dissipation per pole, current-dependent Pvid | 0 W |
| Rated operational current for specified heat dissipation (In) | 0 A |
| Static heat dissipation, non-current-dependent Pvs | 0 W |
| 10.2.2 Corrosion resistance | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | Meets the product standard's requirements. |
| 10.2.5 Lifting | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | Is the panel builder's responsibility. |
| 10.10 Temperature rise | Not applicable. |

| 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. | 10.11 Short-circuit rating | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
|---|-------------------------------------|--|
| | 10.12 Electromagnetic compatibility | |
| | 10.13 Mechanical function | |

Technical data ETIM 9.0

| Low-voltage industrial components (EG000017) / Switch operating shaft (EC000916) | | | |
|--|----|-----|--|
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Switch axle (ecl@ss13-27-37-04-13 [AKF011018]) | | | |
| Length | mm | 480 | |
| Cross section height | mm | 0 | |
| Cross section width | mm | 0 | |