## Empty module for XC100/200 to cover free slots

Powering Business Worldwide\*

Part no. XIOC-NOP 288894

**EL Number** 4519694

(Norway)

Product careire Product careire Product LegislyClopth Carefordame Carefordame Carefordame Carefordame Carefordame Carefordame Carefordame Carefordame Product Tradesiane Product	(INUI Way)	
Part no.  EAN 401080288947 Product beight 100 millimetre Product beight 9 Product beight 9 Product visibil 40 millimetre Product visibil 100 millimetre Product visibil 100 millimetre Product visibil 100 millimetre Product visibil 100 millimetre Cartificacions  U.GSA Class Ro. 222.00 U.GSB CSA CLass Ro. 222.00 U.GSB C	General specifications	
FAM Product langth (Papth Product weight Product weight Product weight Product weight Cartifications  Product Traderame  Product Traderame  Product Sub-Type Accessory  Product Sub-Type Accessory  Product Sub-Type Accessory  Product Sub-Type Accessory  Product Sub-Type  Cartification  Product Sub-Type Accessory  Plug  Cartification  Plug  Cartification  Plug  Pug  Cartification  Plug  Pug  Pug  Pug  Pug  Pug  Pug  Pu	Product name	Eaton XIOC Accessory Plug
Product tageth Personal Similarete Product wight Certifications Certifications Certifications Certifications Certifications CSA Class No. 2252-01 ULBB ULBB ULBB ULBB ULBB ULBB ULBB ULBB	Part no.	XIOC-NOP
Product width Product width Product width Product width Certifications  Product Trademane Product Tradem	EAN	4015082888947
Product width Product weight Certifications Certification Certifications Certification Certific	Product Length/Depth	100 millimetre
Product weight Certifications  CSA Class No. 2252-01 ULS98 USA-C22 No. 1-M ULS98 U	Product height	95 millimetre
Certifications  Certifications  Certifications  Certifications  Certifications  Certifications  Certifications  Certifications  Product Todername  Product Todername  Product Todername  Product Todername  Product Todername  Product Type  Accessory  Product Sub Type  Accessory  Product Sub Type  Product Sub Type  Product Sub Type  Product Todername  Product Sub Type  Product Sub Type  Product Sub Type  Product Todername  Product Sub Type  Product Sub	Product width	30 millimetre
U.SSB C.CZ.2 No. 142-M CSA.CZ2 ZNo. 154-M U.C. Targery Control No.: NRAO CSA. 167-M CSA.CZ2 ZNo. 154-M U.C. Targery Control No.: NRAO CSA. 167-M U.C. Targery Control U.C. Targer	Product weight	0.085 kilogram
Product Type Product Sub Type Product Sub Type Product Sub Type Plug  General information Degree of protection Climatic environmental conditions Ambient operating temperature - min Ambient operating temperature - max Design verification Equipment heat dissipation, current-dependent Pvid Heat dissipation capacity Pdiss UN Heat dissipation capacity Pdiss UN Heat dissipation, capacity Pdiss UN Heat dissipation, capacity Pdiss UN Heat dissipation, non-current-dependent Pvid UN Static heat dissipation, non-current-dependent Pvs UN Heat dissipation of the mail stability of enclosures Weets the product standard's requirements. UN Verification of thermal stability of enclosures Weets the product standard's requirements. UN Verification of resistance of insulating materials to normal heat UN Verification of resistance of insulating materials to normal heat UN Verification of resistance of insulating materials to normal heat UN Verification of resistance of insulating materials to normal heat UN Verification of resistance of insulating materials to normal heat UN Verification of resistance of insulating materials to normal heat UN Verification of resistance of insulating materials to normal heat UN Verification of resistance of insulating materials to normal heat UN Verification of resistance of insulating material UN Verification of resistance of insulating waterial UN Verification of resistance of insulating material UN Verification of resistance of insulating material UN Verification of protection of assemblies UN Verification of switching devices and components UN Verification of switching devices and com	Certifications	UL508 CSA-C22.2 No. 142-M CSA-C22.2 No. 0-M UL CSA UL Category Control No.: NRAQ CSA File No.: 012528 UL File No.: E135462
Product Sub Type  General information  Degree of protection  Climatic environmental conditions  Ambient operating temperature - min Ambient operating temperature - max  Design verification  Equipment heat dissipation, current-dependent Pvid Heat dissipation capacity Pdiss  OW  Heat dissipation capacity Pdiss  OW  Heat dissipation, current-dependent Pvid Attack performance current for specified heat dissipation (in) Static heat dissipation, resistance  10.2.2 Corrosion resistance  10.2.3 Verification of thermal stability of enclosures  10.2.3 Verification of tremal stability of enclosures  10.2.3 Verification of resistance of insulating materials to normal heat  10.2.4 Resistance to ultra-violet (UV) radiation  10.2.5 Lifting  Does not apply, since the entire switchgear needs to be evaluated.  10.2.6 Incorporation a gainst electric shock  Does not apply, since the entire switchgear needs to be evaluated.  10.5 Des not apply, since the entire switchgear needs to be evaluated.  10.6 Incorporation of switching devices and components  10.6 Incorporation of switching devices and components  10.8 Connections for external conductors  10.9.2 Power-frequency electric strength  10.9.3 Impulse withstand voltage  10.9.3 Impulse withstand voltage  10.9.3 Impulse withstand voltage  10.9.3 Impulse withstand voltage  10.9.4 Testing of enclosures made of insulating material  10.10 Temperature rise  The penel builder's responsibility.  10.9.1 Testing of enclosures made of insulating material  10.10 Temperature rise  The penel builder's responsibility.  10.10 Temperature rise  The penel builder's responsibility.  10.10 Temperature rise  The penel builder's responsibility.  11.10 Temperature rise  The penel builder's responsibility.  11.10 Temperature rise	Product Tradename	XIOC
General information  Degree of protection  Climatic environmental conditions  Ambient operating temperature - min Ambient operating temperature - max  55 °C  Design verification  Equipment heat dissipation, current-dependent Pvid Heat dissipation capacity Pdiss Petal dissipation per pole, current-dependent Pvid Heat dissipation per pole, current-dependent Pvid OW Rated operational current for specified heat dissipation (In) Static heat dissipation on-current-dependent Pvs OW Retest dissipation on-current-dependent Pvs OW Retest dissipation on-current for specified heat dissipation (In) Static heat dissipation on-current for specified heat dissipation (In) Static heat dissipation on-current for specified heat dissipation (In) Static heat dissipation, on-current for specified heat dissipation (In) Static heat dissipation, on-current dependent Pvs OW  10.2.2 Corrosion resistance 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements.  10.2.3.2 Verification of resistance of insulating materials to normal heat 10.2.3.3 Resist of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements.  10.2.5 Lifting Does not apply, since the entire switchgear needs to be evaluated.  10.2.6 Mechanical impact Oes not apply, since the entire switchgear needs to be evaluated.  10.2.7 Inscriptions Meets the product standard's requirements.  10.8 Degree of protection of assemblies Meets the product standard's requirements.  10.9 Protection against electric shock Does not apply, since the entire switchgear needs to be evaluated.  10.6 Incorporation of switching devices and components 10.7 Internal electric circuits and connections Is the panel builder's responsibility.  10.9.4 Testing of enclosures made of insulating material 10.10 Tenternal electric shock The panel builder's responsibility.  10.9.4 Testing of enclosures made of insulating material 10.10 Tenternal electric shock The panel builder's responsibility.  10.10 Tenternal electric strong th		Accessory
Degree of protection  Climatic environmental conditions  Ambient operating temperature - min Ambient operating temperature - max  Design verification  Equipment heat dissipation, current-dependent Pvid  Equipment heat dissipation, current-dependent Pvid  Equipment heat dissipation per pole, current-dependent Pvid  Heat dissipation per pole, current-dependent Pvid  Rated operational current for specified heat dissipation (In)  Static heat dissipation, non-current-dependent Pvs  10.2.2 Corresion resistance  Meets the product standard's requirements.  Meets the product standard's requirements.  10.2.3 I Verification of thermal stability of enclosures  Meets the product standard's requirements.  Does not apply, since the entire switchgear needs to be evaluated.  Does not apply, since the entire switchgear needs to be evaluated.  Does not apply, since the entire switchgear needs to be evaluated.  Does not apply, since the entire switchgear needs to be evaluated.  Does not apply, since the entire switchgear needs to be evaluated.  Does not apply, since the entire switchgear needs to be evaluated.  Does not apply, since the entire switchgear needs to be evaluated.  Does not apply, since the entire	Product Sub Type	Plug
Climatic environmental conditions  Ambient operating temperature - min Ambient operating temperature - max  Design verification  Equipment heat dissipation, current-dependent Pvid Heat dissipation, current-dependent Pvid Heat dissipation capacity Pdiss Heat dissipation, current-dependent Pvid  OW Rated operational current for specified heat dissipation (In) Static heat dissipation, non-current-dependent Pvs  OW  10.2.2 Corrosion resistance Meets the product standard's requirements.  10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements.  10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements.  10.2.3 Resist of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements.  10.2.4 Resistance to ultra-violet (UV) radiation Meets the product standard's requirements.  10.2.5 Lifting Does not apply, since the entire switchgear needs to be evaluated.  10.2.6 Mechanical impact Does not apply, since the entire switchgear needs to be evaluated.  10.2 Inscriptions Meets the product standard's requirements.  10.5 Protection against electric shock Does not apply, since the entire switchgear needs to be evaluated.  10.6 Incorporation of switching devices and components Does not apply, since the entire switchgear needs to be evaluated.  10.7 Internal electrical circuits and connections Is the panel builder's responsibility.  10.9.2 Power-frequency electric strength Is the panel builder's responsibility.  10.9.3 Impulse withstand voltage Is the panel builder's responsibility.  10.10 Temperature rise The panel builder's responsibility.	General information	
Ambient operating temperature - min Ambient operating temperature - max 55 °C  Design verification  Equipment heat dissipation, current-dependent Pvid 0 W Heat dissipation capacity Pdiss Heat dissipation capacity Pdiss 0 W Heat dissipation per pole, current-dependent Pvid 0 W Rated operational current for specified heat dissipation (In) Static heat dissipation, non-current-dependent Pvs 0 W 10.22 Corrosion resistance 10.2.3.1 Verification of termal stability of enclosures 10.2.3.2 Verification of resistance of insulating materials to normal heat 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects 10.2.4 Resistance to ultra-violet (UV) radiation 10.2.5 Lifting 10.2.6 Mechanical impact 10.2.6 Mechanical impact 10.2.7 Inscriptions 10.3 Degree of protection of assemblies 10.4 Clearances and creepage distances 10.5 Protection against electric shock 10.5 Protection against electric shock 10.5 Incorporation of switching devices and components 10.5 Protection against electric shock 10.6 Incorporation of switching devices and components 10.7 Internal electrical circuits and connections 10.8 Connections for external conductors 10.9 Power-frequency electric strength 10.9 Testing of enclosures made of insulating material 10.9 The panel builder's responsibility. 10.9.1 Testing of enclosures made of insulating material 10.9 The panel builder's responsibility.	Degree of protection	IP20
Ambient operating temperature - max  Design verification  Equipment heat dissipation, current-dependent Pvid  Heat dissipation capacity Pdiss  OW  Heat dissipation apacity Pdiss  OW  Rated operational current for specified heat dissipation (In)  Static heat dissipation, non-current-dependent Pvid  OW  Rated operational current for specified heat dissipation (In)  OA  Static heat dissipation, non-current-dependent Pvs  OW  10.2.2 Corrosion resistance  Meets the product standard's requirements.  10.2.3.1 Verification of thermal stability of enclosures  Meets the product standard's requirements.  10.2.3.2 Verification of resistance of insulating materials to normal heat  Meets the product standard's requirements.  Meets the product standard's requirements.  10.2.4 Resistance to ultra-violet (UV) radiation  Meets the product standard's requirements.  10.2.5 Lifting  Obes not apply, since the entire switchgear needs to be evaluated.  10.2.7 Inscriptions  Meets the product standard's requirements.  10.3 Degree of protection of assemblies  Meets the product standard's requirements.  Does not apply, since the entire switchgear needs to be evaluated.  Does not apply, since the entire switchgear needs to be evaluated.  Does not apply, since the entire switchgear needs to be evaluated.  Does not apply, since the entire switchgear needs to be evaluated.  Does not apply, since the entire switchgear needs to be evaluated.  10.7 Internal electrical circuits and connections  Is the panel builder's responsibility.  In the	Climatic environmental conditions	
Design verification  Equipment heat dissipation, current-dependent Pvid  Heat dissipation capacity Pdiss  Heat dissipation capacity Pdiss  OW  Rated operational current for specified heat dissipation (In)  Static heat dissipation, non-current-dependent Pvid  OW  10.2.2 Corrosion resistance  Mets the product standard's requirements.  10.2.3.1 Verification of thermal stability of enclosures  Mets the product standard's requirements.  10.2.3.2 Verification of resistance of insulating materials to normal heat  10.2.3.3 Resist, of insul. mat. to abnormal heat/fire by internal elect. effects  Mets the product standard's requirements.  10.2.4 Resistance to ultra-violet (UV) radiation  Mets the product standard's requirements.  10.2.5 Lifting  Does not apply, since the entire switchgear needs to be evaluated.  10.2.7 Inscriptions  Mets the product standard's requirements.  10.3 Degree of protection of assemblies  Mets the product standard's requirements.  Meets the product standard's requirements.  10.4 Clearances and creepage distances  Meets the product standard's requirements.  10.3 Degree of protection of assemblies  Meets the product standard's requirements.  Meets the product standard's requirements.  Meets the product standard's requirements.  Does not apply, since the entire switchgear needs to be evaluated.  10.5 Protection against electric shock  Does not apply, since the entire switchgear needs to be evaluated.  10.6 Incorporation of switching devices and components  Internal electrical circuits and connections  Is the panel builder's responsibility.  Is the panel builder's responsibility.  In the panel builder's responsibility.  In the panel builder's responsibility.  The panel builder's responsibility.	Ambient operating temperature - min	0°C
Equipment heat dissipation, current-dependent Pvid  Heat dissipation capacity Pdiss  OW  Rated operational current for specified heat dissipation (In)  Static heat dissipation, non-current-dependent Pvs  OW  10.2.7 Corrosion resistance  Meets the product standard's requirements.  10.2.3.1 Verification of thermal stability of enclosures  Meets the product standard's requirements.  10.2.3.2 Verification of resistance of insulating materials to normal heat  Meets the product standard's requirements.  10.2.5 Lifting  Does not apply, since the entire switchgear needs to be evaluated.  10.2.7 Inscriptions  Meets the product standard's requirements.  Does not apply, since the entire switchgear needs to be evaluated.  Meets the product standard's requirements.  10.3 Degree of protection of assemblies  Meets the product standard's requirements.  Meets the product standard's requirements.  10.4 Clearances and creepage distances  Meets the product standard's requirements.  10.5 Protection against electric shock  Does not apply, since the entire switchgear needs to be evaluated.  Does not apply, since the entire switchgear needs to be evaluated.  In the panel builder's responsibility.  In the panel builder's responsibility.  In the panel builder's responsibility.  In the panel builder's re	Ambient operating temperature - max	55 °C
Heat dissipation capacity Pdiss  Heat dissipation per pole, current-dependent Pvid  Rated operational current for specified heat dissipation (In)  Static heat dissipation, non-current-dependent Pvs  0 W  10.22 Corrosion resistance  Meets the product standard's requirements.  10.2.3.1 Verification of thermal stability of enclosures  10.2.3.2 Verification of resistance of insulating materials to normal heat  10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects  10.2.4 Resistance to ultra-violet (UV) radiation  10.2.5 Lifting  10.2.6 Mechanical impact  10.2.7 Inscriptions  10.3 Degree of protection of assemblies  10.4 Clearances and creepage distances  10.5 Protection against electric shock  10.5 Protection against electric shock  10.5 Incorporation of switching devices and components  10.6 Incorporation of switching devices and components  10.7 Internal electrical circuits and connections  10.8 Incorporation for external conductors  10.9 Power-frequency electric strength  10.9 Power-frequency electric strength  10.9.1 Tempale builder's responsibility.  10.9.2 Power-frequency electric strength  10.9.3 Impulse withstand voltage  10.9.4 Testing of enclosures made of insulating material  10.10 Temperature rise	Design verification	
Heat dissipation per pole, current-dependent Pvid  Rated operational current for specified heat dissipation (In)  Static heat dissipation, non-current-dependent Pvs  0 W  10.22 Corrosion resistance  10.23.1 Verification of thermal stability of enclosures  10.23.2 Verification of resistance of insulating materials to normal heat  10.23.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects  10.24 Resistance to ultra-violet (UV) radiation  10.25 Lifting  10.26 Mechanical impact  10.27 Inscriptions  10.31 Degree of protection of assemblies  10.4 Clearances and creepage distances  10.4 Clearances and creepage distances  10.5 Protection against electric shock  10.5 Protection against electric shock  10.5 Inscriptions of switching devices and components  10.5 Protection for switching devices and components  10.5 Power-frequency electric strength  10.8 Connections for external conductors  10.9 Power-frequency electric strength  10.9 Power-frequency electric strength  10.9 Is the panel builder's responsibility.  10.9.1 Temperature rise  10.9 The panel builder is responsibility.  10.9.2 The panel builder is responsibility.  10.9.3 Impulse withstand voltage  10.9.4 Testing of enclosures made of insulating material  10.10 Temperature rise	Equipment heat dissipation, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)  Static heat dissipation, non-current-dependent Pvs  10.22 Corrosion resistance  Meets the product standard's requirements.  10.2.3.1 Verification of thermal stability of enclosures  10.2.3.2 Verification of resistance of insulating materials to normal heat  10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects  10.2.4 Resistance to ultra-violet (UV) radiation  10.2.5 Lifting  10.2.6 Mechanical impact  10.2.7 Inscriptions  10.3 Degree of protection of assemblies  10.4 Clearances and creepage distances  10.5 Protection against electric shock  10.6 Incorporation of switching devices and components  10.7 Internal electrical circuits and connections  10.8 Connections for external conductors  10.9 Power-frequency electric strength  10.9.3 Impulse withstand voltage  10.9.4 Testing of enclosures made of insulating material  10.10 Temperature rise  O A  0 W  0 W  0 W  Meets the product standard's requirements.  Does not apply, since the entire switchgear needs to be evaluated.  Does not apply, since the entire switchgear needs to be evaluated.  10.6 Incorporation of switching devices and components  10.8 Connections for external conductors  1 Is the panel builder's responsibility.  1 Is the panel builder's responsibility.  1 Is the panel builder is responsibility.  1 The panel builder is responsibility.  The panel builder is responsibility.	Heat dissipation capacity Pdiss	0 W
Static heat dissipation, non-current-dependent Pvs  10.22 Corrosion resistance  Meets the product standard's requirements.  10.2.3.1 Verification of thermal stability of enclosures  Meets the product standard's requirements.  10.2.3.2 Verification of resistance of insulating materials to normal heat  10.2.3.3 Resist of insul. mat. to abnormal heat/fire by internal elect. effects  Meets the product standard's requirements.  10.2.4 Resistance to ultra-violet (UV) radiation  Meets the product standard's requirements.  10.2.5 Lifting  Does not apply, since the entire switchgear needs to be evaluated.  10.2.7 Inscriptions  Meets the product standard's requirements.  10.3 Degree of protection of assemblies  Meets the product standard's requirements.  10.4 Clearances and creepage distances  Meets the product standard's requirements.  10.5 Protection against electric shock  Does not apply, since the entire switchgear needs to be evaluated.  10.6 Incorporation of switching devices and components  Does not apply, since the entire switchgear needs to be evaluated.  10.7 Internal electrical circuits and connections  Is the panel builder's responsibility.  10.9.2 Power-frequency electric strength  Is the panel builder's responsibility.  10.9.3 Impulse withstand voltage  Is the panel builder's responsibility.  10.9.4 Testing of enclosures made of insulating material  Is the panel builder's responsibility.  10.10 Temperature rise  The panel builder's responsibile for the temperature rise calculation. Eaton will the panel builder is responsible for the temperature rise calculation.	Heat dissipation per pole, current-dependent Pvid	0 W
Meets the product standard's requirements.  10.2.3.1 Verification of thermal stability of enclosures  10.2.3.2 Verification of resistance of insulating materials to normal heat  10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects  10.2.4 Resistance to ultra-violet (UV) radiation  10.2.5 Lifting  10.2.5 Lifting  10.2.6 Mechanical impact  10.2.7 Inscriptions  10.3 Degree of protection of assemblies  10.4 Clearances and creepage distances  10.4 Clearances and creepage distances  10.5 Protection against electric shock  10.6 Incorporation of switching devices and components  10.7 Internal electrical circuits and connections  10.8 Connections for external conductors  10.9.2 Power-frequency electric strength  10.9.3 Impulse withstand voltage  10.9.4 Testing of enclosures made of insulating material  10.9.1 Temperature rise  Meets the product standard's requirements.	Rated operational current for specified heat dissipation (In)	0 A
10.2.3.1 Verification of thermal stability of enclosures  10.2.3.2 Verification of resistance of insulating materials to normal heat  10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects  10.2.4 Resistance to ultra-violet (UV) radiation  10.2.5 Lifting  10.2.6 Mechanical impact  10.2.7 Inscriptions  10.3 Degree of protection of assemblies  10.4 Clearances and creepage distances  10.5 Protection against electric shock  10.5 Protection against electric shock  10.6 Incorporation of switching devices and components  10.7 Internal electrical circuits and connections  10.8 Connections for external conductors  10.9 Power-frequency electric strength  10.9.3 Impulse withstand voltage  10.9.4 Testing of enclosures made of insulating material  10.10 Temperature rise  Meets the product standard's requirements.  Does not apply, since the entire switchgear needs to be evaluated.  Does not apply, since the entire switchgear needs to be evaluated.  10.5 Protection against electric shock  10.6 Incorporation of switching devices and components  10.7 Internal electrical circuits and connections  10.8 Connections for external conductors  10.9 Power-frequency electric strength  10.9 Power-frequency electric strength  10.9 Is the panel builder's responsibility.  10.9 Is the panel builder's responsibility.  10.9 The panel builder's responsibility.  10.9 The panel builder is responsibility.  10.9 The panel builder is responsibility.	Static heat dissipation, non-current-dependent Pvs	0 W
10.2.3.2 Verification of resistance of insulating materials to normal heat 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects 10.2.4 Resistance to ultra-violet (UV) radiation 10.2.5 Lifting 10.2.5 Lifting 10.2.6 Mechanical impact 10.2.7 Inscriptions 10.2.7 Inscriptions 10.3 Degree of protection of assemblies 10.4 Clearances and creepage distances 10.4 Clearances and creepage distances 10.5 Protection against electric shock 10.6 Incorporation of switching devices and components 10.7 Internal electrical circuits and connections 10.8 Connections for external conductors 10.9 Power-frequency electric strength 10.9.3 Impulse withstand voltage 10.9.4 Testing of enclosures made of insulating material 10.10 Temperature rise 10.10 Temperature rise 10.2.5 Verification of several encountering the temperature rise calculation. Eaton will the product standard's requirements. 10.5 Protection against electric shock 10.6 Incorporation of switching devices and components 10.7 Internal electrical circuits and connections 10.8 Connections for external conductors 10.9 Power-frequency electric strength 10.9 Internal electric	10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects  10.2.4 Resistance to ultra-violet (UV) radiation  Meets the product standard's requirements.  10.2.5 Lifting  Does not apply, since the entire switchgear needs to be evaluated.  10.2.6 Mechanical impact  10.2.7 Inscriptions  Meets the product standard's requirements.  10.3 Degree of protection of assemblies  Meets the product standard's requirements.  Does not apply, since the entire switchgear needs to be evaluated.  Does not apply, since the entire switchgear needs to be evaluated.  Does not apply, since the entire switchgear needs to be evaluated.  In the panel builder's responsibility.  Does not apply, since the entire switchgear needs to be evaluated.  In the panel builder's responsibility.  Does not apply, since the entire switchgear needs to be evaluated.  In the panel builder's responsibility.  Does not apply, since the entire switchgear needs to be evaluated.  In the panel builder's responsibility.  Does not apply, since the entire switchgear needs to be evaluated.  In the panel builder's responsibility.  Does not apply, since the entire switchgear needs to be evaluated.  In the panel builder's responsibility.  In the panel builder's responsibility.  The panel builder's responsibility.  The panel builder's responsibility.	10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
Meets the product standard's requirements.  10.2.5 Lifting Does not apply, since the entire switchgear needs to be evaluated.  10.2.6 Mechanical impact Does not apply, since the entire switchgear needs to be evaluated.  10.2.7 Inscriptions Meets the product standard's requirements.  10.3 Degree of protection of assemblies Meets the product standard's requirements.  10.4 Clearances and creepage distances Meets the product standard's requirements.  10.5 Protection against electric shock Does not apply, since the entire switchgear needs to be evaluated.  10.6 Incorporation of switching devices and components Does not apply, since the entire switchgear needs to be evaluated.  10.7 Internal electrical circuits and connections Is the panel builder's responsibility.  10.9.2 Power-frequency electric strength Is the panel builder's responsibility.  10.9.3 Impulse withstand voltage Is the panel builder's responsibility.  10.9.4 Testing of enclosures made of insulating material Is the panel builder is responsibility.  10.10 Temperature rise The panel builder is responsibile for the temperature rise calculation. Eaton will	10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.5 Lifting  10.2.6 Mechanical impact  10.2.6 Mechanical impact  10.2.7 Inscriptions  10.3 Degree of protection of assemblies  10.4 Clearances and creepage distances  10.5 Protection against electric shock  10.6 Incorporation of switching devices and components  10.7 Internal electrical circuits and connections  10.8 Connections for external conductors  10.9 Power-frequency electric strength  10.9.1 Power-frequency electric strength  10.9.2 Power-frequency electric strength  10.9.4 Testing of enclosures made of insulating material  10.10 Temperature rise  10.20 Sonot apply, since the entire switchgear needs to be evaluated.  10.5 Incorporation of switching devices and components  10.6 Lectronal apply, since the entire switchgear needs to be evaluated.  10.7 Internal electrical circuits and connections  10.8 Lectronal apply, since the entire switchgear needs to be evaluated.  10.9 Is the panel builder's responsibility.  10.9 Is the panel builder's responsibility.  10.9 Is the panel builder's responsibility.  10.9 Temperature rise  10.9 The panel builder is responsibility.  10.10 Temperature rise  10.9 The panel builder is responsibility.  10.10 Temperature rise  10.10 Temperature rise	10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.6 Mechanical impact  10.2.7 Inscriptions  Meets the product standard's requirements.  10.3 Degree of protection of assemblies  Meets the product standard's requirements.  Does not apply, since the entire switchgear needs to be evaluated.  Does not apply, since the entire switchgear needs to be evaluated.  Incomposition of switching devices and components  Does not apply, since the entire switchgear needs to be evaluated.  Incomposition of switching devices and components  Is the panel builder's responsibility.  Does not apply, since the entire switchgear needs to be evaluated.  Incomposition of switching devices and components  Is the panel builder's responsibility.  Does not apply, since the entire switchgear needs to be evaluated.  Is the panel builder's responsibility.  Incomposition of switching devices and components  Is the panel builder's responsibility.  Incomposition of switching devices and components  Is the panel builder's responsibility.  The panel builder is responsibility.  The panel builder is responsibility.	10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.7 Inscriptions  10.3 Degree of protection of assemblies  10.4 Clearances and creepage distances  10.5 Protection against electric shock  10.6 Incorporation of switching devices and components  10.7 Internal electrical circuits and connections  10.8 Connections for external conductors  10.9.2 Power-frequency electric strength  10.9.3 Impulse withstand voltage  10.9.4 Testing of enclosures made of insulating material  10.10 Temperature rise  Meets the product standard's requirements.  Does not apply, since the entire switchgear needs to be evaluated.  Is the panel builder's responsibility.  It the panel builder's responsibility.  The panel builder's responsibility.	10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.3 Degree of protection of assemblies  10.4 Clearances and creepage distances  10.5 Protection against electric shock  10.6 Incorporation of switching devices and components  10.7 Internal electrical circuits and connections  10.8 Connections for external conductors  10.9.2 Power-frequency electric strength  10.9.3 Impulse withstand voltage  10.9.4 Testing of enclosures made of insulating material  10.10 Temperature rise  Meets the product standard's requirements.  Does not apply, since the entire switchgear needs to be evaluated.  Is the panel builder's responsibility.  The panel builder is responsible for the temperature rise calculation. Eaton will	10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances  10.5 Protection against electric shock  10.6 Incorporation of switching devices and components  10.7 Internal electrical circuits and connections  10.8 Connections for external conductors  10.9.2 Power-frequency electric strength  10.9.3 Impulse withstand voltage  10.9.4 Testing of enclosures made of insulating material  10.10 Temperature rise  Meets the product standard's requirements.  Does not apply, since the entire switchgear needs to be evaluated.  Is the panel builder's responsibility.  The panel builder is responsible for the temperature rise calculation. Eaton will	10.2.7 Inscriptions	Meets the product standard's requirements.
10.5 Protection against electric shock  10.6 Incorporation of switching devices and components  10.7 Internal electrical circuits and connections  10.8 Connections for external conductors  10.9.2 Power-frequency electric strength  10.9.3 Impulse withstand voltage  10.9.4 Testing of enclosures made of insulating material  10.9.5 Protection against electric shock  Does not apply, since the entire switchgear needs to be evaluated.  Is the panel builder's responsibility.  The panel builder is responsible for the temperature rise calculation. Eaton will	10.3 Degree of protection of assemblies	Meets the product standard's requirements.
10.6 Incorporation of switching devices and components  Does not apply, since the entire switchgear needs to be evaluated.  10.7 Internal electrical circuits and connections  Is the panel builder's responsibility.  10.8 Connections for external conductors  Is the panel builder's responsibility.  10.9.2 Power-frequency electric strength  Is the panel builder's responsibility.  10.9.3 Impulse withstand voltage  Is the panel builder's responsibility.  10.9.4 Testing of enclosures made of insulating material  Is the panel builder's responsibility.  10.10 Temperature rise  The panel builder is responsible for the temperature rise calculation. Eaton will	10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.7 Internal electrical circuits and connections  Is the panel builder's responsibility.  10.8 Connections for external conductors  Is the panel builder's responsibility.  10.9.2 Power-frequency electric strength  Is the panel builder's responsibility.  10.9.3 Impulse withstand voltage  Is the panel builder's responsibility.  10.9.4 Testing of enclosures made of insulating material  Is the panel builder's responsibility.  10.10 Temperature rise  The panel builder is responsible for the temperature rise calculation. Eaton will	10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.8 Connections for external conductors  Is the panel builder's responsibility.  10.9.2 Power-frequency electric strength  Is the panel builder's responsibility.  10.9.3 Impulse withstand voltage  Is the panel builder's responsibility.  10.9.4 Testing of enclosures made of insulating material  Is the panel builder's responsibility.  10.10 Temperature rise  The panel builder is responsible for the temperature rise calculation. Eaton will	10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.9.2 Power-frequency electric strength  10.9.3 Impulse withstand voltage  10.9.4 Testing of enclosures made of insulating material  10.9.4 Testing of enclosures made of insulating material  10.10 Temperature rise	10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage  1s the panel builder's responsibility.  10.9.4 Testing of enclosures made of insulating material  1s the panel builder's responsibility.  10.10 Temperature rise  The panel builder is responsible for the temperature rise calculation. Eaton will	10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material Is the panel builder's responsibility.  10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will	10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.10 Temperature rise  The panel builder is responsible for the temperature rise calculation. Eaton will	10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
	10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
	10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating	Is the panel builder's responsibility.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Programmable logic controllers PLC (EG000024) / Accessories/spare parts for controls (EC002584)		
Electric engineering, automation, process control engineering / Display and control component / Panel (HMI) / Panel (HMI, accessories) (ecl@ss13-27-33-02-92 [AFX005008])		
Type of electrical accessory/spare part	Plug	
Type of mechanical accessory/spare part	Cover	
Accessory	Yes	
Spare part	No	