

**Busbar support 250A**

**Part no.**                    **BPZ-BBS-4/250**  
**289868**  
**EL Number**                **2473262**  
**(Norway)**

<b>General specifications</b>		
Product name		Eaton xEnergy Basic other accessory
Part no.		BPZ-BBS-4/250
EAN		4015082898687
Product Length/Depth		150 millimetre
Product height		40 millimetre
Product width		50 millimetre
Product weight		0.078 kilogram
Compliances		RoHS conform
Product Tradename		xEnergy Basic
Product Type		Accessories
Product Sub Type		Other
<b>Delivery program</b>		
Amperage rating		250 A
Number of poles		Four-pole
<b>Technical Data - Electrical</b>		
Current rating - max		250 A
Rated short-time withstand current (I <sub>cw</sub> )		15 kA
<b>Technical Data - Mechanical</b>		
Mounting method		Surface mounting Floor standing distribution board
Mounting position		Universal
Material		Plastic
Busbar distance		20 mm
Busbar height		5 mm
Busbar position		Bottom rear
Busbar thickness - max		20 mm
<b>Additional information</b>		
Functions		Additional equipment

**Technical data ETIM 9.0**

Energy distribution systems (EG000015) / Distributor assembly busbars (EC001896)		
Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Distributor assembly busbars (ecl@ss13-27-40-06-10 [AC0383016])		
Height	mm	40
Width	mm	50
Depth	mm	150
With cover		No
Number of poles		4
Busbar distance	mm	20
Busbar height	mm	5
Busbar thickness	mm	20
Max. rated current	A	250
Short-circuit breaking capacity (I <sub>cw</sub> )	kA	15
Busbar position		Bottom rear