DATASHEET - CI/E-PKZ01-XSVB



Padlocking feature, yellow, for expansion/installation housing with PKZ01 $\,$



Part no. CI/E-PKZ01-XSVB Catalog No. 289939

Delivery program

Product range	Accessories
Accessories	Withdrawable modules for insulated enclosures
	Can be locked in 0 position
Degree of Protection	Front IP65
For use with	PKZM01 +NHI-E +U or A +L (2 off)
Notes Combinable with CI-PKZ01-X and E-PKZ01-X.	

Design verification as per IEC/EN 61439

In	Α	0
P _{vid}	W	0
P _{vid}	W	0
P _{vs}	W	0
P _{diss}	W	0
	°C	-25
	°C	70
		Meets the product standard's requirements.
		Meets the product standard's requirements.
		Meets the product standard's requirements.
		Meets the product standard's requirements.
		Please enquire
		Does not apply, since the entire switchgear needs to be evaluated.
		Does not apply, since the entire switchgear needs to be evaluated.
		Meets the product standard's requirements.
		Does not apply, since the entire switchgear needs to be evaluated.
		Meets the product standard's requirements.
		Does not apply, since the entire switchgear needs to be evaluated.
		Does not apply, since the entire switchgear needs to be evaluated.
		Is the panel builder's responsibility.
		Is the panel builder's responsibility.
		Is the panel builder's responsibility.
		Is the panel builder's responsibility.
		Is the panel builder's responsibility.
		Not applicable.
		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
	P _{vid} P _{vid} P _{vs} P _{diss}	P _{vid} W P _{vid} W P _{vs} W P _{diss} W °C °C

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Empty enclosure for switchgear (EC000712)					
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Empty housing for switch devices (ecl@ss10.0.1-27-37-13-01 [AKN343014])					
Material housing		Plastic			
Width	mm	70			
Height	mm	71			
Depth	mm	32.5			
With transparent cover		No			
Suitable for emergency stop		No			
Model		Surface mounting			
Degree of protection (IP)		IP65			
Degree of protection (NEMA)		Other			

Approvals

Additional product information (links)

IL03402009Z (AWA1210-2261) CI enclosure kits for PKZ01 surface/flush mounting		
IL03402009Z (AWA1210-2261) CI enclosure kits for PKZ01 surface/flush mounting	ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL03402009Z2018_05.pdf	
Motor starters and "Special Purpose Ratings" for the North American market	http://www.eaton.eu/ecm/groups/public/@pub/@europe/@electrical/documents/content/pct_3258146.pdf	
Busbar Component Adapters for modern Industrial control panels	http://www.moeller.net/binary/ver_techpapers/ver960en.pdf	