

Label, for 2 position switch, blank

**Part no.** M22-XCK3  
**290260**

**EL Number**  
**(Norway)** 4315313

<b>General specifications</b>		
Product name		Eaton Moeller® series M22 Accessory Label for 4-position switch
Part no.		M22-XCK3
EAN		4015082902605
Product Length/Depth		50 millimetre
Product height		2 millimetre
Product width		50 millimetre
Product weight		0.004 kilogram
Compliances		Contact Manufacturer
Certifications		UL/CSA certification not required IEC/EN 60947 VDE 0660 LR DNV GL
Product Tradename		M22
Product Type		Accessory
Product Sub Type		Label for 4-position switch
<b>Features &amp; Functions</b>		
Color		Silver
Inscription		Other 2 direction arrows, can be turned through 90°
Language		Other
Shape		Square
<b>General information</b>		
Used with		Two-position joystick M22-D4... M22-DI4... M22-WJ... M22-WRJ... M22S-WJ... M22S-WRJ...
<b>Ambient conditions, mechanical</b>		
Mounting position		As required
<b>Climatic environmental conditions</b>		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Climatic proofing		Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
<b>Communication</b>		
Connection to SmartWire-DT		No
<b>Design verification</b>		
Equipment heat dissipation, current-dependent P <sub>vid</sub>		0 W
Heat dissipation capacity P <sub>diss</sub>		0 W
Heat dissipation per pole, current-dependent P <sub>vid</sub>		0 W
Rated operational current for specified heat dissipation (I <sub>n</sub> )		0 A
Static heat dissipation, non-current-dependent P <sub>vs</sub>		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire

10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		Not applicable.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Text plate for command devices (EC000624)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Identification plate for command devices (ecl@ss13-27-37-12-25 [AKF043019])

Literal imprint		Other
Language of the imprint		Other
Imprint ISO symbols		Symbol "Arrow"
Colour		Silver
Shape		Square
Width	mm	50
Height	mm	2
Outer diameter	mm	0