



PE/N terminal kit, max. 63A, 2 x 25 mm² + 27 x 16 mm²

Part no. BFZ-TS-KL29
Catalog No. 293631

Delivery program

| | | | |
|----------------|--|--|-------------------------|
| Basic function | | | Accessory consideration |
| Accessories | | | BF |
| Product range | | | BF flat DB0 |

Technical data ETIM 7.0

| | | | |
|--|--|----|----------|
| Energy distribution systems (EG000015) / Rail terminal bar (EC000275) | | | |
| Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Rail terminal bar clamp (ec@ss10.0.1-27-40-06-03 [AC0369011]) | | | |
| Number of poles | | | 1 |
| Nominal current | | A | 63 |
| Connection type | | | Screwing |
| Mounting method | | | Screw |
| Number of connections total | | | 29 |
| Number of connections < 6 mm ² | | | 0 |
| Number of connections 10 mm ² | | | 0 |
| Number of connections 16 mm ² | | | 27 |
| Number of connections 25 mm ² | | | 2 |
| Number of connections > 25 mm ² | | | 0 |
| Number of connections < AWG 6 | | | 0 |
| Number of connections AWG 6 | | | 0 |
| Number of connections AWG 4 | | | 0 |
| Number of connections AWG 2 | | | 0 |
| Number of connections AWG 4/0 | | | 0 |
| Number of connections 250 kcmil | | | 0 |
| Number of connections > 250 kcmil | | | 0 |
| Contact safe | | | No |
| Height | | mm | 8 |
| Width | | mm | 60 |
| Depth | | mm | 220 |

Additional product information (links)

| | |
|------------------------|---|
| Product overview (Web) | http://www.eaton.eu/DE/Europe/Electrical/ProductsServices/Residential/index.htm |
|------------------------|---|