

46TBR100

| | | |
|-----------------------------|--|--|
| Product name | | Eaton Busmann series medium voltage expulsion fuse |
| Part no. | | 46TBR100 |
| EAN | | 5027590481731 |
| Product Length/Depth | | 225 millimetre |
| Product height | | 76 millimetre |
| Product width | | 106 millimetre |
| Product weight | | 0.142 gram |
| Compliances | | Contact Manufacturer |
| Certifications | | ANSI/IEEE Std C37.42 |
| Product Tradename | | None |
| Product Type | | Medium voltage expulsion fuse |
| Product Sub Type | | None |
| Amperage Rating | | 100 A |
| Voltage rating | | 46 kV |
| Current characteristic type | | Type T - Complies with ANSI C 37-42 requirements for slow acting T characteristics |
| Rated frequency - min | | 50 Hz |
| Rated frequency - max | | 60 Hz |
| Application | | Primary side transformer protection, feeder protection, capacitor bank protection |
| Standard | | ANSI |
| Type of termination | | Removable buttonhead |

Technical data ETIM 8.0

| | | |
|--|----|----------------------|
| Circuit breakers and fuses (EG000020) / Expulsion fuse-link, medium voltage (EC003611) | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Safety fuse systems (unspecified) (ecl@ss10.0.1-27-14-21-90 [BAB265011]) | | |
| Rated current | A | 100 |
| Rated voltage | kV | 46 |
| Voltage type | | AC |
| Rated frequency | Hz | 50 - 60 |
| Release characteristic | | T |
| Type of termination | | Removable buttonhead |
| Standard | | ANSI |