



Fuse-link, medium voltage, 125 A, AC 7.2 kV, 40 kA, 3", 76 x 292 mm, back-up, DIN, with striker

Part no. 7.2KV 125Amp 3" 'J' DIN Fuse
 Catalog No. 7.2TFLSJ125

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			medium voltage
Rated current	I	A	125
Rated voltage			AC 7.2 kV
Construction size			3"
Size			76 x 292 mm
Utilization category			back-up
Status indicator			with striker
Breaking Capacity		kA	40
usable for size/applications			transformer protection indoor or outdoor use
Standard/Approval			DIN
Standards/Regulations			DIN 43625 VDE 0670-4 VDE 0670-402 IEC 60282-1

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507)			
Rated current		A	25
Rated voltage		kV	7.2
Voltage type			AC
Rated frequency		Hz	50 - 50
Breaking capacity		kA	40
Utilization category			Other
Application			Primary side transformer protection
Length		mm	292
Diameter		mm	76
Performance category according to IEC 60282-1			Back-up
With striker			Yes
Standard			DIN
Release characteristic			Other
Installation technique			Air