

Non-standard switch, T3, 32 A, flush mounting, 8 contact unit(s)



Part no. **T3-8-SOND*/E**
907857

| General specifications | |
|---|--|
| Product name | Eaton Moeller® series T3 Non-standard switch |
| Part no. | T3-8-SOND*/E |
| Product Length/Depth | 160 millimetre |
| Product height | 54 millimetre |
| Product width | 61 millimetre |
| Product weight | 0.412 kilogram |
| Certifications | IEC/EN 60947 VDE 0660 IEC/EN 60947-3 IEC/EN 60204 |
| Product Tradename | T3 |
| Product Type | Non-standard switch |
| Product Sub Type | None |
| Catalog Notes | Customized version according to form Rated Short-time Withstand Current (Icw) for a time of 1 second |
| General information | |
| Degree of protection | NEMA 12 |
| Degree of protection (front side) | IP65 |
| Lifespan, mechanical | 500,000 Operations |
| Mounting method | Flush mounting |
| Mounting position | As required |
| Number of contact units | 8 |
| Operating frequency | 1200 Operations/h |
| Overvoltage category | III |
| Pollution degree | 3 |
| Rated impulse withstand voltage (Uimp) | 6000 V AC |
| Safe isolation | 440 V AC, Between the contacts, According to EN 61140 |
| Safety parameter (EN ISO 13849-1) | B10d values as per EN ISO 13849-1, table C.1 |
| Shock resistance | 15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms |
| Suitable for | Front mounting 4-hole |
| Climatic environmental conditions | |
| Ambient operating temperature - min | -25 °C |
| Ambient operating temperature - max | 50 °C |
| Ambient operating temperature (enclosed) - min | -25 °C |
| Ambient operating temperature (enclosed) - max | 40 °C |
| Climatic proofing | Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78 |
| Terminal capacities | |
| Terminal capacity | 1 x (1 - 6) mm ² , solid or stranded 2 x (1 - 6) mm ² , solid or stranded 1 x (0.75 - 4) mm ² , flexible with ferrules to DIN 46228 2 x (0.75 - 4) mm ² , flexible with ferrules to DIN 46228 |
| Screw size | M4, Terminal screw |
| Electrical rating | |
| Rated breaking capacity at 220/230 V (cos phi to IEC 60947-3) | 260 A |
| Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3) | 260 A |
| Rated breaking capacity at 500 V (cos phi to IEC 60947-3) | 240 A |
| Rated breaking capacity at 660/690 V (cos phi to IEC 60947-3) | 170 A |
| Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V | 23.7 A |
| Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V | 23.7 A |

| | | |
|--|--|---|
| Rated operational current (Ie) at AC-3, 500 V | | 23.7 A |
| Rated operational current (Ie) at AC-3, 660 V, 690 V | | 14.7 A |
| Rated operational current (Ie) at AC-21, 440 V | | 32 A |
| Rated operational current (Ie) at AC-23A, 230 V | | 32 A |
| Rated operational current (Ie) at AC-23A, 400 V, 415 V | | 32 A |
| Rated operational current (Ie) at AC-23A, 500 V | | 26.4 A |
| Rated operational current (Ie) at AC-23A, 690 V | | 17 A |
| Rated operational current (Ie) at DC-1, load-break switches I/r = 1 ms | | 25 A |
| Rated operational current (Ie) at DC-13, control switches L/R = 50 ms | | 20 A |
| Rated operational current (Ie) at DC-21, 240 V | | 1 A |
| Rated operational current (Ie) at DC-23A, 24 V | | 25 A |
| Rated operational current (Ie) at DC-23A, 48 V | | 25 A |
| Rated operational current (Ie) at DC-23A, 60 V | | 25 A |
| Rated operational current (Ie) at DC-23A, 120 V | | 12 A |
| Rated operational current (Ie) at DC-23A, 240 V | | 5 A |
| Rated operational current (Ie) star-delta at AC-3, 220/230 V | | 32 A |
| Rated operational current (Ie) star-delta at AC-3, 380/400 V | | 32 A |
| Rated operational current (Ie) star-delta at AC-3, 500 V | | 32 A |
| Rated operational current (Ie) star-delta at AC-3, 690 V | | 25.5 A |
| Rated operational power at AC-3, 380/400 V, 50 Hz | | 11 kW |
| Rated operational power at AC-3, 415 V, 50 Hz | | 11 kW |
| Rated operational power at AC-3, 500 V, 50 Hz | | 15 kW |
| Rated operational power at AC-3, 690 V, 50 Hz | | 11 kW |
| Rated operational power at AC-23A, 220/230 V, 50 Hz | | 7.5 kW |
| Rated operational power at AC-23A, 400 V, 50 Hz | | 15 kW |
| Rated operational power at AC-23A, 500 V, 50 Hz | | 15 kW |
| Rated operational power at AC-23A, 690 V, 50 Hz | | 15 kW |
| Rated operational power star-delta at 220/230 V, 50 Hz | | 7.5 kW |
| Rated operational power star-delta at 380/400 V, 50 Hz | | 15 kW |
| Rated operational power star-delta at 500 V, 50 Hz | | 18.5 kW |
| Rated operational power star-delta at 690 V, 50 Hz | | 22 kW |
| Rated uninterrupted current (Iu) | | 32 A |
| Short-circuit rating | | |
| Rated conditional short-circuit current (Iq) | | 1 kA |
| Rated short-time withstand current (Icw) | | 650 A, Contacts, 1 second 0.65 kA |
| Short-circuit protection rating | | 35 A gG/gL, Fuse, Contacts |
| Switching capacity | | |
| Load rating | | 1.3 x I# (with intermittent operation class 12, 60 % duty factor) 2 x I# (with intermittent operation class 12, 25 % duty factor) 1.6 x I# (with intermittent operation class 12, 40 % duty factor) |
| Number of contacts in series at DC-21A, 240 V | | 1 |
| Number of contacts in series at DC-23A, 24 V | | 1 |
| Number of contacts in series at DC-23A, 48 V | | 2 |
| Number of contacts in series at DC-23A, 60 V | | 3 |
| Number of contacts in series at DC-23A, 120 V | | 3 |
| Number of contacts in series at DC-23A, 240 V | | 5 |
| Rated making capacity up to 690 V (cos phi to IEC/EN 60947-3) | | 320 A |
| Contacts | | |
| Control circuit reliability | | 1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA) |
| Number of auxiliary contacts (change-over contacts) | | 0 |
| Number of auxiliary contacts (normally closed contacts) | | 0 |
| Number of auxiliary contacts (normally open contacts) | | 0 |
| Actuator | | |
| Actuator color | | Black |

| | | |
|--|--|--|
| Actuator type | | Short thumb-grip |
| Design verification | | |
| Equipment heat dissipation, current-dependent Pvid | | 1.1 W |
| Heat dissipation capacity Pdiss | | 0 W |
| Heat dissipation per pole, current-dependent Pvid | | 1.1 W |
| Rated operational current for specified heat dissipation (In) | | 32 A |
| Static heat dissipation, non-current-dependent Pvs | | 0 W |
| 10.2.2 Corrosion resistance | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | UV resistance only in connection with protective shield. |
| 10.2.5 Lifting | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 9.0

| | | |
|---|----|-----------|
| Low-voltage industrial components (EG000017) / Switch disconnecter (low voltage) (EC000216) | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Switch disconnecter (ec1@ss13-27-37-14-03 [AKF060018]) | | |
| Version as main switch | | No |
| Version as maintenance-/service switch | | No |
| Version as safety switch | | No |
| Version as emergency stop installation | | No |
| Version as reversing switch | | No |
| Number of switches | | 1 |
| Max. rated operation voltage Ue AC | V | |
| Rated operating voltage | V | 690 - 690 |
| Rated permanent current Iu | A | 32 |
| Rated permanent current at AC-23, 400 V | A | 32 |
| Rated permanent current at AC-21, 400 V | A | 32 |
| Rated operation power at AC-3, 400 V | kW | 11 |
| Rated short-time withstand current Icw | kA | 0.65 |
| Rated operation power at AC-23, 400 V | kW | 15 |
| Switching power at 400 V | kW | 15 |
| Conditioned rated short-circuit current Iq | kA | 1 |
| Number of poles | | |
| Number of auxiliary contacts as normally closed contact | | 0 |
| Number of auxiliary contacts as normally open contact | | 0 |
| Number of auxiliary contacts as change-over contact | | 0 |

| | | | |
|---|--|----|--|
| Motor drive optional | | | No |
| Motor drive integrated | | | No |
| Voltage release optional | | | No |
| Device construction | | | Built-in device fixed built-in technique |
| Suitable for floor mounting | | | No |
| Suitable for front mounting 4-hole | | | Yes |
| Suitable for front mounting centre | | | No |
| Suitable for distribution board installation | | | No |
| Suitable for intermediate mounting | | | No |
| Colour control element | | | Black |
| Type of control element | | | Short thumb-grip |
| Interlockable | | | No |
| Type of electrical connection of main circuit | | | Screw connection |
| With pre-assembled cabling | | | No |
| Degree of protection (IP), front side | | | IP65 |
| Degree of protection (NEMA) | | | 12 |
| Width | | mm | 61 |
| Height | | mm | 54 |
| Depth | | mm | 160 |
| Width in number of modular spacings | | | |