

# DATASHEET - 1A 240V PLUG TOP FUSE



**Fuse-link, Overcurrent NON SMD, 1 A, AC 240 V, 6 kA, BS1362 plug fuse, 6.3 x 25 mm, gL/gG, BS**



**Part no. 1A 240V PLUG TOP FUSE**  
**Catalog No. C180-1A**

Similar to illustration

## Delivery program

|                              |   |    |                       |
|------------------------------|---|----|-----------------------|
| Product range                |   |    | Fuse                  |
| Basic function               |   |    | Fuse-link             |
| Field of application         |   |    | Overcurrent NON SMD   |
| Rated current                | I | A  | 1                     |
| Rated voltage                |   |    | AC 240 V              |
| Construction size            |   |    | BS1362 plug fuse      |
| Size                         |   |    | 6.3 x 25 mm           |
| Utilization category         |   |    | gL/gG                 |
| Breaking Capacity            |   | kA | 6                     |
| usable for size/applications |   |    | use in BS1363 plugs   |
| Standard/Approval            |   |    | BS                    |
| Shape                        |   |    | cylindrical           |
| Standards/Regulations        |   |    | BS1362<br>IEC 60269-3 |

## Technical data ETIM 7.0

|   |  |   |              |
|---|--|---|--------------|
| Circuit breakers and fuses (EG000020) / Miniature fuse (EC000035)   |  |   |              |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015]) |  |   |              |
| Connection type   |  |   | Other        |
| Voltage type  |  |   | AC           |
| Release characteristic  |  |   | Fast (F)     |
| Model   |  |   | Ceramic fuse |
| Rated current   |  | A | 1            |
| Rated voltage   |  | V | 240          |
| Dimensions  |  |   | Other        |
| Optical defect indication   |  |   | No           |