



Fuse-link, LV, 20 A, AC 690 V, 22 x 58 mm, gL/gG, IEC

**EL Number**  
**(Norway)**

**C22G20**  
**1600221**

Product name	Eaton Bussmann series low voltage cylindrical fuse
Part no.	C22G20
EAN	5027590495349
Product Length/Depth	58 millimetre
Product height	22.2 millimetre
Product width	22.2 millimetre
Product weight	54.1 gram
Compliances	RoHS Compliant CE Marked
Certifications	IEC 60269
Product Tradename	None
Product Type	Low voltage cylindrical fuse
Product Sub Type	None
Amperage Rating	20 A
Voltage rating	690 V
Voltage type	AC
Breaking capacity	80 kA
Utilization category	gL/gG (cable protection/equipment protection)
Suitable for	CH22 Modular fuse holder

### Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015])		
Model		Ceramic fuse
Size		22x58 mm
Voltage type		AC
Rated current	A	20
Rated voltage	V	690
Utilization category		gL/gG (cable protection/equipment protection)
Rated operating frequency	Hz	45 - 62
Type of fuse status indicator		Other
Release characteristic		Other
Breaking capacity	kA	80
Power loss at rated current	W	2.7