

DATASHEET - 3P+N 22X58 NEON INDICATOR FUSE HOLDER



Fuse-holder, low voltage, 125 A, AC 690 V, 22 x 58 mm, 3P+N, IEC, With indicator



Part no. **3P+N 22x58 Neon Indicator Fuse Holder**
Catalog No. **CH223DNIU**

Delivery program

| | | | |
|-----------------------|---|---|----------------|
| Product range | | | Fuse |
| Basic function | | | Fuse-holder |
| Field of application | | | low voltage |
| Rated current | I | A | 125 |
| Rated voltage | | | AC 690 V |
| Size | | | 22 x 58 mm |
| Status indicator | | | Neon indicator |
| Number of poles | | | 3P + N |
| Standard/Approval | | | IEC |
| Standards/Regulations | | | IEC 60269-2 |

Technical data ETIM 7.0

| | | | |
|--|--|----|----------|
| Circuit breakers and fuses (EG000020) / Holder for cylindrical fuse (EC002705) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Holder for cylindrical fuse (ecl@ss10.0.1-27-14-21-21 [ADI305007]) | | | |
| Nominal voltage | | V | 690 |
| Mounting method | | | DIN rail |
| For fuse size | | | 22x58 mm |
| Number of poles | | | 3 |
| Concurrently switching N-neutral | | | No |
| Lockable | | | Yes |
| Optical defect indication | | | Yes |
| Width in number of modular spacings | | | 8 |
| Built-in depth | | mm | 51.5 |
| Degree of protection (IP) | | | IP20 |