

EPDU MA 1U (C20 16A 1P)8XC13



Catalog No. EMAH28

Similar to illustration

Delivery program

Type		Rack PDU
Input Connection		C20
Cord Length		3m
Input Voltage		200-240V
Phase		Single-phase
Frequency Rating		50/60 Hz
Ethernet Interface		Yes
Serial Interface		Yes
Form Factor		1U
Outlet Control		Yes
Operating Temperature		0° to 60°C (32° to 140°F)
Outlets		8XC13
Number of Outputs C13		8
Number of Outputs C19		0
Amperage Rating		16A
Mounting Direction		Horizontal
ETIM Class		EC002762
Fitted With:		Ampere Meter Display Mounting material
Electrical Connection		Connecting cord with plug
Evaluation		At distance
Mounting Dimension (metrical)		203
Mounting Dimension (standardised)		482.6 mm (19 inch)
Switchable		Yes
Over Voltage Category		2
Wattage		3.84 kW max
Communication		HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS
SNMP		Yes
Mass Configuration		Yes
Package Contents		PDU mounting accessories network cable configuration cable splitter for daisy-chaining Quickstart Safety Instructions
Number of Outputs C20		0
Num of Outputs PC (SCHUKO)		0
Number of Outputs (Other)		0
Number of Outlets with Earth Pin		8

Color		Black
-------	--	-------

Technical data ETIM 7.0

Domestic switching devices (EG000013) / Power distribution unit (PDU) (EC002762)		
Electric engineering, automation, process control engineering / Electrical installation, device / Low-voltage distribution system (mobile) / Low-voltage distribution systems (mobile, unspecified) (ecl@ss10.0.1-27-14-26-90 [AKN612013])		
Mounting dimension (standardised)		482.6 mm (19 inch)
Mounting dimension	mm	
Mounting direction		Horizontal
Electrical connection		Connecting cord with plug
Type of electric connection		C20
Cable length	m	3
Number of socket outlets with protective contact		0
Number of socket outlets with earth pin		8
Number of C13 socket outlets		8
Number of C19 socket outlets		0
Number of C20 socket outlets		0
Number of UK BS1363 sockets		
number of socket outlets swiss standard type 13		
number of socket outlets swiss standard type 15		
number of socket outlets swiss standard type 23		
number of socket outlets swiss standard type 25		
Number of other socket outlets		
Number of height units		
Length	mm	445
Width	mm	44
Height	mm	203
Depth	mm	445
Supply voltage	V	
Over voltage category		2
Mains filter		No
Switchable		Yes
SNMP		Yes
With display		Yes
Evaluation		At distance
With LED indication		No
With fuse		No
Ampere meter		Yes
With temperature measurement		No
With mounting material		Yes