

Eaton EP-401615

Eaton Moeller® series M22 Adapter for PCB contact elements (M22-KP...), 4 mounting locations



Specifiche generali

PRODUCT NAME	Eaton Moeller® series M22 mounting adapter
---------------------	---

CATALOG NUMBER	EP-401615
-----------------------	-----------

EAN	4015082971779
------------	---------------

PRODUCT LENGTH/DEPTH	40.85 mm
-----------------------------	----------

PRODUCT HEIGHT	18.9 mm
-----------------------	---------

PRODUCT WIDTH	39.95 mm
----------------------	----------

PRODUCT WEIGHT	0.004 kg
-----------------------	----------

CERTIFICATIONS	CE RoHS REACH
-----------------------	---------------------

MODEL CODE	M22-AP4
-------------------	---------

Condizioni ambientali e climatiche

AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78

Comunicazione

CONNECTION TO SMARTWIRE-DT	No
-----------------------------------	----

Verifiche di progetto

10.10 TEMPERATURE RISE	Not applicable.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.

Informazioni generali

ACCESSORY/SPARE PART TYPE	Accessory
TYPE	Mounting clamp (front mounting) for 4-contact LED elements

10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.

Risorse

ISTRUZIONI DI INSTALLAZIONE	eaton-rmq-on-pcb-il047033zu.pdf
MCAD MODEL	eaton-pushbutton-and-switch-renewal-parts-accessory-mcad-3d-models-m22-ap4.stp eaton-pushbutton-and-switch-renewal-parts-accessory-mcad-drawings-m22-ap4.dwg

NOME DEL PROGETTO:

NUMERO DEL PROGETTO:

PREPARATO DA:

DATA:



Eaton Corporation plc Eaton House
 30 Pembroke Road
 Dublino 4, Irlanda
 Eaton.com

© 2026 Eaton. Tutti i diritti riservati.

Seguici sui social media per avere informazioni aggiornate sui prodotti e sull'assistenza.

