



**Fuse-link, 450 A, AC 550 V, DC 400 V, 80 kA, BS88, 74 x 262 mm, gL/gG, BS**



**Part no. 450AMP 550V AC / 400V DC**  
**Catalog No. FG450**

Similar to illustration

## Delivery program

Product range			Fuse
Basic function			Fuse-link
Rated current	I	A	450
Rated voltage			AC 550 V DC 400 V
Construction size			BS88
Size			74 x 262 mm
Utilization category			gL/gG
Breaking Capacity		kA	80
usable for size/applications			general industrial applications
Standard/Approval			BS
Shape			centre-bolted tags
Material			Ceramic body
Standards/Regulations			BS88-2

## Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	450
Rated voltage		V	550
Voltage type			AC/DC
Rated switching capacity		kA	80
Utilization category			gL/gG (cable protection/equipment protection)
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No