



Fuse-link, high speed, 45 A, AC 150 V, DC 150 V, 100 kA, 21 x 51 mm, aR, UL



Powering Business Worldwide™

Part no. SEMI-COND FUSE 45A 150V AC
Catalog No. FWA-45A21F

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	45
Rated voltage			AC 150 V DC 150 V
Size			21 x 51 mm
Utilization category			aR
Breaking Capacity		kA	100
usable for size/applications			DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
Standard/Approval			UL
Shape			cylindrical
Standards/Regulations			UL 248

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013])			
Size			Other
Rated voltage		V	150 - 150
Rated voltage			Other
Voltage type			AC/DC
Utilization category			aR (accompanied semiconductor protection)
Rated operating frequency		Hz	45 - 62
Nominal current		A	45
With striker			No
Release characteristic			Other
Breaking capacity		kA	200