



Fuse-link, high speed, 80 A, AC 700 V, 200 kA, 22 x 58 mm, aR, UL

Part no. **80AMP 700V ac 22 X 58MM FERRULE**  
 Catalog No. **FWP-80A22F**

### Delivery program

|                              |   |    |  |
|------------------------------|---|----|--|
| Product range                |   |    | Fuse   |
| Basic function               |   |    | Fuse-link  |
| Field of application         |   |    | high speed   |
| Rated current                | I | A  | 80   |
| Rated voltage                |   |    | AC 700 V   |
| Size                         |   |    | 22 x 58 mm   |
| Utilization category         |   |    | aR   |
| Breaking Capacity            |   | kA | 200  |
| usable for size/applications |   |    | protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters |
| Standard/Approval            |   |    | UL   |
| Shape                        |   |    | cylindrical  |
| Standards/Regulations        |   |    | UL 248   |
| Optional accessories         |   |    | fuse-holder CH221B   |

### Technical data ETIM 7.0

|   |  |    |   |
|---|--|----|---|
| Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)   |  |    |   |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013]) |  |    |   |
| Size  |  |    | 22x58 mm                                  |
| Rated voltage   |  | V  | 700 - 700                                 |
| Rated voltage   |  |    | Other                                     |
| Voltage type  |  |    | AC/DC                                     |
| Utilization category  |  |    | aR (accompanied semiconductor protection) |
| Rated operating frequency   |  | Hz | 45 - 62                                   |
| Nominal current   |  | A  | 80  |
| With striker  |  |    | No  |
| Release characteristic  |  |    | Other                                     |
| Breaking capacity   |  | kA | 200                                       |