



Fuse-link, high speed, 90 A, AC 250 V, 200 kA, 31 x 80 mm, UL

Part no. BUSS HIGH SPEED FUSE
Catalog No. FWX-90A

Similar to illustration

Delivery program

| | | | |
|------------------------------|---|----|--|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | high speed |
| Rated current | I | A | 90 |
| Rated voltage | | | AC 250 V |
| Size | | | 31 x 80 mm |
| Breaking Capacity | | kA | 200 |
| usable for size/applications | | | DC common bus, DC drives, power converters/rectifiers and reduced voltage starters |
| Standard/Approval | | | UL |
| Shape | | | cylindrical with centre-bolted tags |
| Standards/Regulations | | | UL |

Technical data ETIM 7.0

| | | | |
|---|--|----|-------|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) | | | |
| Construction size | | | Other |
| Rated current | | A | 90 |
| Rated voltage | | V | 250 |
| Voltage type | | | AC |
| Rated switching capacity | | kA | 200 |
| Utilization category | | | Other |
| Type of fuse status indicator | | | None |
| Insulated metal gripping lugs (IMGL) | | | No |

Additional product information (links)

| | |
|-------------------------|---|
| Product datasheet (pdf) | http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_720005_FWX-(35-2500)A.pdf |
|-------------------------|---|