



Fuse-link, low voltage, 710 A, AC 550 V, DC 250 V, 80 kA, BS88, 83 x 262 mm, gL/gG, BS, IEC

Part no. **710AMP 550V AC / 250V DC**  
Catalog No. **GG710**

### Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	710
Rated voltage			AC 550 V DC 250 V
Construction size			BS88
Size			83 x 262 mm
Utilization category			gL/gG
Breaking Capacity		kA	80
usable for size/applications			motor protection
Standard/Approval			BS IEC
Shape			cylindrical with centre-bolted tags
Standards/Regulations			BS88 IEC 60269

### Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	710
Rated voltage		V	550
Voltage type			AC
Rated switching capacity		kA	80
Utilization category			Other
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No