



Fuse-link, high speed, 680 A, AC 1000 V, BS88, 80 x 180 mm, aR, BS, ultra rapid



Part no. GSMK 680A 1000V AC FUSE LINK- SFE8350680
Catalog No. GSMK680

Delivery program

| | | | |
|----------------------|---|---|--------------------|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | high speed |
| Rated current | I | A | 680 |
| Rated voltage | | | AC 1000 V |
| Construction size | | | BS88 |
| Size | | | 80 x 180 mm |
| Utilization category | | | aR |
| Standard/Approval | | | BS |
| Shape | | | offset bolted tags |

Technical data ETIM 7.0

| | | | |
|---|--|----|---|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) | | | |
| Construction size | | | Other |
| Rated current | | A | 680 |
| Rated voltage | | V | 1000 |
| Voltage type | | | AC |
| Rated switching capacity | | kA | 100 |
| Utilization category | | | aR (accompanied semiconductor protection) |
| Type of fuse status indicator | | | None |
| Insulated metal gripping lugs (IMGL) | | | No |