

Fuse-block, low voltage, 60 A, AC 600 V, UL Class J, 55 x 58 x 87 mm, 2P, UL, CSA

Part no. **REPLACED BY JM60060-2CR**
Catalog No. **J60060-2CR**

Delivery program

Product range			Fuse accessory
Basic function			Fuse-block
Field of application			low voltage
Rated current	I	A	60
Rated voltage			AC 600 V
Construction size			UL Class J
Size			55 x 58 x 87 mm
Breaking Capacity		kA	200
Number of poles			2P
Standard/Approval			UL CSA
Material			Thermoplastic
Standards/Regulations			UL Recognized, Guide No. IZLT2, File No. E14853
Optional accessories			IP20 finger-safe cover

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse base (EC000067)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Low-Voltage HRC fuse base (ecl@ss10.0.1-27-14-21-06 [AKE278013])			
Construction size			Other
Number of poles			2
Rated current		A	60
Bus-mounting type			No
Swivelling mechanism			No

Additional product information (links)

Product datasheet (pdf)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-a/Bus_Ele_DS_1114_J600_Series.pdf
-------------------------	---